



## List 10052

EXOTAP® DC VP-DC-HT, DIN Overall Length

STRAIGHT FLUTE	VC10	V	C/1.5P	0°	PACKED 1 PIECE
----------------	------	---	--------	----	-------------------



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	Ik (Inch)	
1005200108	● 1/4 - 20 UNC	H3	3.150	0.598	1.181	0.255	0.191	0.313	4
1005200208	● 1/4 - 20 UNC	H5	3.150	0.598	1.181	0.255	0.191	0.313	4
1005200308	● 1/4 - 28 UNF	H3	3.150	0.598	1.181	0.255	0.191	0.313	4
1005200408	● 5/16 - 18 UNC	H3	3.543	0.665	1.377	0.318	0.238	0.375	4
1005200508	● 5/16 - 18 UNC	H5	3.543	0.665	1.377	0.318	0.238	0.375	4
1005200608	● 5/16 - 24 UNF	H3	3.543	0.665	1.377	0.318	0.238	0.375	4
1005200708	● 3/8 - 16 UNC	H3	3.937	0.751	1.377	0.381	0.286	0.438	4
1005200808	● 3/8 - 16 UNC	H5	3.937	0.751	1.377	0.381	0.286	0.438	4
1005200908	● 3/8 - 24 UNF	H3	3.937	0.751	1.377	0.381	0.286	0.438	4
1005201008	● 7/16 - 14 UNC	H3	3.937	0.858	1.712	0.323	0.242	0.406	4
1005201108	● 7/16 - 14 UNC	H5	3.937	0.858	1.712	0.323	0.242	0.406	4
1005201208	● 7/16 - 20 UNF	H3	3.937	0.858	1.712	0.323	0.242	0.406	4
1005201308	● 7/16 - 20 UNF	H5	3.937	0.858	1.712	0.323	0.242	0.406	4
1005201408	● 1/2 - 13 UNC	H3	4.331	0.921	1.933	0.367	0.275	0.438	4
1005201508	● 1/2 - 13 UNC	H5	4.331	0.921	1.933	0.367	0.275	0.438	4
1005201608	● 1/2 - 20 UNF	H3	3.937	0.921	1.933	0.367	0.275	0.438	4
1005201708	● 1/2 - 20 UNF	H5	3.937	0.921	1.933	0.367	0.275	0.438	4
1005201808	● 9/16 - 12 UNC	H3	4.331	1.000	1.972	0.429	0.322	0.500	5
1005201908	● 9/16 - 12 UNC	H5	4.331	1.000	1.972	0.429	0.322	0.500	5
1005202008	● 9/16 - 18 UNF	H3	3.937	1.000	1.972	0.429	0.322	0.500	5
1005202108	● 9/16 - 18 UNF	H5	3.937	1.000	1.972	0.429	0.322	0.500	5
1005202208	● 5/8 - 11 UNC	H3	4.331	1.090	2.125	0.480	0.360	0.563	5
1005202308	● 5/8 - 11 UNC	H5	4.331	1.090	2.125	0.480	0.360	0.563	5
1005202408	● 5/8 - 18 UNF	H3	3.937	1.090	2.125	0.480	0.360	0.563	5
1005202508	● 5/8 - 18 UNF	H5	3.937	1.090	2.125	0.480	0.360	0.563	5
1005202608	● 3/4 - 10 UNC	H3	4.921	1.200	2.433	0.590	0.442	0.688	5
1005202708	● 3/4 - 10 UNC	H5	4.921	1.200	2.433	0.590	0.442	0.688	5
1005202808	● 3/4 - 16 UNF	H3	4.331	1.200	2.433	0.590	0.442	0.688	5
1005202908	● 3/4 - 16 UNF	H5	4.331	1.200	2.433	0.590	0.442	0.688	5
1005203008	● 7/8 - 9 UNC	H3	5.512	1.334	2.653	0.697	0.523	0.750	5
1005203108	● 7/8 - 9 UNC	H5	5.512	1.334	2.653	0.697	0.523	0.750	5
1005203208	● 7/8 - 14 UNF	H3	4.921	1.334	2.653	0.697	0.523	0.750	5
1005203308	● 7/8 - 14 UNF	H5	4.921	1.334	2.653	0.697	0.523	0.750	5
1005203408	● 1 - 8 UNC	H3	6.299	1.500	3.011	0.800	0.600	0.813	5
1005203508	● 1 - 8 UNC	H5	6.299	1.500	3.011	0.800	0.600	0.813	5

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel			Aluminum		Nickel Alloy	Titanium							
Low	Medium	High			300	400					17-4 PH	6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1045	1065	4140	4340		○		○								
1018	1045	1065					25-75 SFM		40-65 SFM								

○ Good ○ Best

