




List 10053

EXOTAP® DC-OIL VPO-DC-HT, DIN Overall Length

STRAIGHT FLUTE	VC10	V		C/1.5P	0°	PACKED 1 PIECE
----------------	------	---	--	--------	----	-------------------



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)		
1005300108	●	1/4 - 20 UNC	H3	3.150	0.598	1.181	0.255	0.191	0.313	4
1005300208	●	1/4 - 20 UNC	H5	3.150	0.598	1.181	0.255	0.191	0.313	4
1005300308	●	1/4 - 28 UNF	H3	3.150	0.598	1.181	0.255	0.191	0.313	4
1005300408	●	5/16 - 18 UNC	H3	3.543	0.665	1.377	0.318	0.238	0.375	4
1005300508	●	5/16 - 18 UNC	H5	3.543	0.665	1.377	0.318	0.238	0.375	4
1005300608	●	5/16 - 24 UNF	H3	3.543	0.665	1.377	0.318	0.238	0.375	4
1005300708	●	3/8 - 16 UNC	H3	3.937	0.751	1.377	0.381	0.286	0.438	4
1005300808	●	3/8 - 16 UNC	H5	3.937	0.751	1.377	0.381	0.286	0.438	4
1005300908	●	3/8 - 24 UNF	H3	3.937	0.751	1.377	0.381	0.286	0.438	4
1005301008	●	7/16 - 14 UNC	H3	3.937	0.858	1.712	0.323	0.242	0.406	4
1005301108	●	7/16 - 14 UNC	H5	3.937	0.858	1.712	0.323	0.242	0.406	4
1005301208	●	7/16 - 20 UNF	H3	3.937	0.858	1.712	0.323	0.242	0.406	4
1005301308	●	7/16 - 20 UNF	H5	3.937	0.858	1.712	0.323	0.242	0.406	4
1005301408	●	1/2 - 13 UNC	H3	4.331	0.921	1.933	0.367	0.275	0.438	4
1005301508	●	1/2 - 13 UNC	H5	4.331	0.921	1.933	0.367	0.275	0.438	4
1005301608	●	1/2 - 20 UNF	H3	3.937	0.921	1.933	0.367	0.275	0.438	4
1005301708	●	1/2 - 20 UNF	H5	3.937	0.921	1.933	0.367	0.275	0.438	4
1005301808	●	9/16 - 12 UNC	H3	4.331	1.000	1.972	0.429	0.322	0.500	5
1005301908	●	9/16 - 12 UNC	H5	4.331	1.000	1.972	0.429	0.322	0.500	5
1005302008	●	9/16 - 18 UNF	H3	3.937	1.000	1.972	0.429	0.322	0.500	5
1005302108	●	9/16 - 18 UNF	H5	3.937	1.000	1.972	0.429	0.322	0.500	5
1005302208	●	5/8 - 11 UNC	H3	4.331	1.090	2.125	0.480	0.360	0.563	5
1005302308	●	5/8 - 11 UNC	H5	4.331	1.090	2.125	0.480	0.360	0.563	5
1005302408	●	5/8 - 18 UNF	H3	3.937	1.090	2.125	0.480	0.360	0.563	5
1005302508	●	5/8 - 18 UNF	H5	3.937	1.090	2.125	0.480	0.360	0.563	5
1005302608	●	3/4 - 10 UNC	H3	4.921	1.200	2.433	0.590	0.442	0.688	5
1005302708	●	3/4 - 10 UNC	H5	4.921	1.200	2.433	0.590	0.442	0.688	5
1005302808	●	3/4 - 16 UNF	H3	4.331	1.200	2.433	0.590	0.442	0.688	5
1005302908	●	3/4 - 16 UNF	H5	4.331	1.200	2.433	0.590	0.442	0.688	5
1005303008	●	7/8 - 9 UNC	H3	5.512	1.334	2.653	0.697	0.523	0.750	5
1005303108	●	7/8 - 9 UNC	H5	5.512	1.334	2.653	0.697	0.523	0.750	5
1005303208	●	7/8 - 14 UNF	H3	4.921	1.334	2.653	0.697	0.523	0.750	5
1005303308	●	7/8 - 14 UNF	H5	4.921	1.334	2.653	0.697	0.523	0.750	5
1005303408	●	1 - 8 UNC	H3	6.299	1.500	3.011	0.800	0.600	0.813	5
1005303508	●	1 - 8 UNC	H5	6.299	1.500	3.011	0.800	0.600	0.813	5

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel			Aluminum		Nickel Alloy	Titanium									
Low	Medium	High			300	400	17-4 PH				6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1045	1065	4140	4340														
1018	1045	1065						⊙		⊙									
								40-100 SFM		50-110 SFM									

○ Good ⊙ Best

