




List 10056

EXOTAP® DC VP-DC-HT

STRAIGHT FLUTE	VC10	V	C/1.5P	0°	PACKED 1 PIECE
----------------	------	---	--------	----	-------------------



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)		
1005600108	●	1/4 - 20 UNC	H3	2.500	0.598	1.000	0.255	0.191	0.313	4
1005600208	●	1/4 - 20 UNC	H5	2.500	0.598	1.000	0.255	0.191	0.313	4
1005600308	●	1/4 - 28 UNF	H3	2.500	0.598	1.000	0.255	0.191	0.313	4
1005600408	●	5/16 - 18 UNC	H3	2.720	0.665	1.125	0.318	0.238	0.375	4
1005600508	●	5/16 - 18 UNC	H5	2.720	0.665	1.125	0.318	0.238	0.375	4
1005600608	●	5/16 - 24 UNF	H3	2.720	0.665	1.125	0.318	0.238	0.375	4
1005600708	●	3/8 - 16 UNC	H3	2.930	0.751	1.251	0.381	0.286	0.438	4
1005600808	●	3/8 - 16 UNC	H5	2.930	0.751	1.251	0.381	0.286	0.438	4
1005600908	●	3/8 - 24 UNF	H3	2.930	0.751	1.251	0.381	0.286	0.438	4
1005601008	●	7/16 - 14 UNC	H3	3.150	0.858	1.712	0.323	0.242	0.406	4
1005601108	●	7/16 - 14 UNC	H5	3.150	0.858	1.712	0.323	0.242	0.406	4
1005601208	●	7/16 - 20 UNF	H3	3.150	0.858	1.712	0.323	0.242	0.406	4
1005601308	●	7/16 - 20 UNF	H5	3.150	0.858	1.712	0.323	0.242	0.406	4
1005601408	●	1/2 - 13 UNC	H3	3.370	0.921	1.933	0.367	0.275	0.438	4
1005601508	●	1/2 - 13 UNC	H5	3.370	0.921	1.933	0.367	0.275	0.438	4
1005601608	●	1/2 - 20 UNF	H3	3.370	0.921	1.933	0.367	0.275	0.438	4
1005601708	●	1/2 - 20 UNF	H5	3.370	0.921	1.933	0.367	0.275	0.438	4
1005601808	●	9/16 - 12 UNC	H3	3.590	1.000	1.972	0.429	0.322	0.500	5
1005601908	●	9/16 - 12 UNC	H5	3.590	1.000	1.972	0.429	0.322	0.500	5
1005602008	●	9/16 - 18 UNF	H3	3.590	1.000	1.972	0.429	0.322	0.500	5
1005602108	●	9/16 - 18 UNF	H5	3.590	1.000	1.972	0.429	0.322	0.500	5
1005602208	●	5/8 - 11 UNC	H3	3.810	1.090	2.125	0.480	0.360	0.563	5
1005602308	●	5/8 - 11 UNC	H5	3.810	1.090	2.125	0.480	0.360	0.563	5
1005602408	●	5/8 - 18 UNF	H3	3.810	1.090	2.125	0.480	0.360	0.563	5
1005602508	●	5/8 - 18 UNF	H5	3.810	1.090	2.125	0.480	0.360	0.563	5
1005602608	●	3/4 - 10 UNC	H3	4.250	1.200	2.433	0.590	0.442	0.688	5
1005602708	●	3/4 - 10 UNC	H5	4.250	1.200	2.433	0.590	0.442	0.688	5
1005602808	●	3/4 - 16 UNF	H3	4.250	1.200	2.433	0.590	0.442	0.688	5
1005602908	●	3/4 - 16 UNF	H5	4.250	1.200	2.433	0.590	0.442	0.688	5

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High							6061	Casting			Inconel	6Al4V	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1045	1065	4140	4340	300	400	17-4 PH		6061 7075								
1018	1045	1065	4140	4340					○		○							
									25-75 SFM		40-65 SFM							

○ Good ○ Best



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX