



List 11017

HY-PRO® V-DIN, DIN Overall Length

SPIRAL POINT	HSSE	V	C/4P	0°	PACKED 1 PIECE
--------------	------	---	------	----	-------------------



EDP		Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
				L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1101700108	●	No. 4 - 40 UNC	H2	2.205	0.303	0.713	0.141	0.110	0.188	2
1101700208	●	No. 6 - 32 UNC	H3	2.205	0.378	0.791	0.141	0.110	0.188	2
1101700308	●	No. 8 - 32 UNC	H3	2.480	0.382	0.835	0.168	0.131	0.250	3
1101700408	●	No. 10 - 24 UNC	H3	2.756	0.500	0.984	0.194	0.152	0.250	3
1101700508	●	No. 10 - 32 UNF	H3	2.756	0.500	0.992	0.194	0.152	0.250	3
1101700608	●	1/4 - 20 UNC	H3	3.150	0.602	1.185	0.255	0.191	0.313	3
1101700708	●	1/4 - 28 UNF	H3	3.150	0.602	1.197	0.255	0.191	0.313	3
1101700808	●	5/16 - 18 UNC	H3	3.543	0.669	1.382	0.318	0.238	0.375	3
1101700908	●	5/16 - 24 UNF	H3	3.543	0.669	1.390	0.318	0.238	0.375	3
1101701008	●	3/8 - 16 UNC	H3	3.937	0.760	1.386	0.381	0.286	0.438	3
1101701108	●	3/8 - 24 UNF	H3	3.937	0.760	1.398	0.381	0.286	0.438	3
1101701208	●	7/16 - 14 UNC	H3	3.937	0.894	1.291	0.323	0.242	0.406	3
1101701308	●	7/16 - 20 UNF	H3	3.937	0.858	1.291	0.323	0.242	0.406	3
1101701408	●	1/2 - 13 UNC	H3	4.331	0.961	1.354	0.367	0.275	0.438	3
1101701508	●	1/2 - 20 UNF	H3	3.937	0.921	1.354	0.367	0.275	0.438	3

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	○	○	○	○	○	○	○					○			
50-90 SFM	40-80 SFM	40-60 SFM	40-80 SFM	20-60 SFM	40-80 SFM	40-80 SFM	30-50 SFM	30-80 SFM					20-60 SFM			

○ Good ○ Best

