




## List 13014

HY-PRO® HXL-SFT, Horizontal Applications, DIN Overall Length

SPIRAL FLUTE	HSSE	S/O	C/2.5P	15°	PACKED 1 PIECE
--------------	------	-----	--------	-----	-------------------



EDP Number	Thread Size	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
		L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	Lk (Inch)		
1301402601	●	1/2 - 13 UNC	4.331	0.614	-	0.367	0.275	0.438	4
1301402701	●	1/2 - 20 UNF	3.937	0.614	1.000	0.367	0.275	0.438	4
1301400101	●	9/16 - 12 UNC	4.331	0.665	-	0.429	0.322	0.500	4
1301400201	●	9/16 - 18 UNF	3.937	0.665	1.126	0.429	0.322	0.500	4
1301400301	●	5/8 - 11 UNC	4.331	0.728	-	0.480	0.360	0.563	4
1301400401	●	5/8 - 18 UNF	3.937	0.728	1.252	0.480	0.360	0.563	4
1301400501	●	3/4 - 10 UNC	4.921	0.799	-	0.590	0.442	0.688	4
1301402801	●	3/4 - 16 UNF	4.331	0.799	1.500	0.590	0.442	0.688	4
1301400601	●	7/8 - 9 UNC	5.512	0.890	-	0.697	0.523	0.750	4
1301402901	●	7/8 - 14 UNF	4.921	0.890	1.752	0.697	0.523	0.750	4
1301400701	●	1 - 8 UNC	6.299	1.000	-	0.800	0.600	0.813	5
1301403001	●	1 - 12 UNF	5.512	0.665	2.000	0.800	0.600	0.813	5
1301400901	●	1 - 1/8 - 7 UNC	7.087	1.142	-	0.896	0.672	0.875	5
1301401101	●	1 - 1/8 - 8 UN	7.087	1.000	2.252	0.896	0.672	0.875	5
1301403101	●	1 - 1/8 - 12 UNF	5.906	0.665	2.252	0.896	0.672	0.875	5
1301401201	●	1 - 1/4 - 7 UNC	7.087	1.142	2.500	1.021	0.766	1.000	5
1301401401	●	1 - 1/4 - 8 UN	7.087	1.000	2.500	1.021	0.766	1.000	5
1301403201	●	1 - 1/4 - 12 UNF	5.906	0.665	2.500	1.021	0.766	1.000	5
1301401501	●	1 - 3/8 - 6 UNC	7.874	1.335	-	1.108	0.831	1.063	5
1301401701	●	1 - 3/8 - 8 UN	7.874	1.000	2.752	1.108	0.831	1.063	5
1301403901	●	1 - 3/8 - 12 UNF	6.693	1.000	2.752	1.108	0.831	1.063	5
1301401801	●	1 - 1/2 - 6 UNC	7.874	1.335	-	1.233	0.925	1.125	5
1301402001	●	1 - 1/2 - 8 UN	7.874	1.000	3.000	1.233	0.925	1.125	5
1301403301	●	1 - 1/2 - 12 UNF	6.693	0.665	3.000	1.233	0.925	1.125	5
1301402101	●	1 - 5/8 - 8 UN	7.874	1.000	3.252	1.305	0.979	1.125	6
1301403501	●	1 - 3/4 - 5 UNC	8.661	1.598	-	1.430	1.072	1.250	6
1301402201	●	1 - 3/4 - 8 UN	7.874	1.000	3.500	1.430	1.072	1.250	6
1301402301	●	1 - 7/8 - 8 UN	8.858	1.000	3.752	1.519	1.139	1.250	6
1301403601	●	2 - 4.5 UNC	9.843	1.780	-	1.644	1.233	1.375	6
1301402401	●	2 - 8 UN	8.858	1.000	4.000	1.644	1.233	1.375	6
1301403701	●	2 - 1/4 - 4.5 UNC	11.024	1.780	-	1.894	1.420	1.438	6
1301404001	●	2 - 1/4 - 8 UN	9.843	1.000	4.500	1.894	1.420	1.438	6
1301403801	●	2 - 1/2 - 4 UNC	12.402	2.000	-	2.100	1.575	1.500	6
1301402501	●	2 - 1/2 - 8 UN	10.827	1.000	5.000	2.100	1.575	1.500	6

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	○	○	○	○					○	○		
1018	1045				○	○	○	○					○	○		
25-80 SFM	20-50 SFM	20-45 SFM	20-50 SFM	15-20 SFM	20-45 SFM	20-45 SFM	15-20 SFM	25-75 SFM					15-35 SFM	8-15 SFM		

○ Good ○ Best



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX