




HY-PRO® VXL-OIL

Ideal for Oil Field Applications

List 13025

HY-PRO® VXL-OIL-SFT, Vertical Applications, DIN Overall Length



EDP Number	Thread Size	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
		L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)		
1302502601	●	1/2 - 13 UNC	4.331	0.614	-	0.367	0.275	0.438	3
1302502701	●	1/2 - 20 UNF	3.937	0.614	1.000	0.367	0.275	0.438	4
1302500101	●	9/16 - 12 UNC	4.331	0.665	-	0.429	0.322	0.500	4
1302500201	●	9/16 - 18 UNF	3.937	0.665	1.125	0.429	0.322	0.500	4
1302500301	●	5/8 - 11 UNC	4.331	0.728	-	0.480	0.360	0.563	4
1302500401	●	5/8 - 18 UNF	3.937	0.728	1.251	0.480	0.360	0.563	4
1302500501	●	3/4 - 10 UNC	4.921	0.799	-	0.590	0.442	0.688	4
1302502801	●	3/4 - 16 UNF	4.331	0.799	1.500	0.590	0.442	0.688	4
1302500601	●	7/8 - 9 UNC	5.512	0.889	-	0.697	0.523	0.750	4
1302502901	●	7/8 - 14 UNF	4.921	0.889	1.751	0.697	0.523	0.750	4
1302500701	●	1 - 8 UNC	6.299	1.000	-	0.800	0.600	0.813	4
1302503001	●	1 - 12 UNF	5.512	0.665	2.000	0.800	0.600	0.813	4
1302500901	●	1 - 1/8 - 7 UNC	7.087	1.141	-	0.896	0.672	0.875	4
1302501101	●	1 - 1/8 - 8 UN	7.087	1.000	2.251	0.896	0.672	0.875	4
1302503101	●	1 - 1/8 - 12 UNF	5.906	0.665	2.251	0.896	0.672	0.875	5
1302501201	●	1 - 1/4 - 7 UNC	7.087	1.141	2.500	1.021	0.766	1.000	5
1302501401	●	1 - 1/4 - 8 UN	7.087	1.000	2.500	1.021	0.766	1.000	5
1302503201	●	1 - 1/4 - 12 UNF	5.906	0.665	2.500	1.021	0.766	1.000	5
1302501501	●	1 - 3/8 - 6 UNC	7.874	1.334	-	1.108	0.831	1.063	5
1302501701	●	1 - 3/8 - 8 UN	7.874	1.000	2.751	1.108	0.831	1.063	5
1302503901	●	1 - 3/8 - 12 UNF	6.693	1.000	2.751	1.108	0.831	1.063	5
1302501801	●	1 - 1/2 - 6 UNC	7.874	1.334	-	1.233	0.925	1.125	5
1302502001	●	1 - 1/2 - 8 UN	7.874	1.000	3.000	1.233	0.925	1.125	5
1302503301	●	1 - 1/2 - 12 UNF	6.693	0.665	3.000	1.233	0.925	1.125	5
1302502101	●	1 - 5/8 - 8 UN	7.874	1.000	3.252	1.305	0.979	1.125	6
1302503501	●	1 - 3/4 - 5 UNC	8.661	1.598	-	1.430	1.072	1.250	6
1302502201	●	1 - 3/4 - 8 UN	7.874	1.000	3.500	1.430	1.072	1.250	6
1302502301	●	1 - 7/8 - 8 UN	8.858	1.000	3.752	1.519	1.139	1.250	6
1302503601	●	2 - 4.5 UNC	9.843	1.779	-	1.644	1.233	1.375	6
1302502401	●	2 - 8 UN	8.858	1.000	4.000	1.644	1.233	1.375	6
1302503701	●	2 - 1/4 - 4.5 UNC	11.024	1.779	-	1.894	1.420	1.438	6
1302504001	●	2 - 1/4 - 8 UN	9.843	1.000	4.500	1.894	1.420	1.438	6
1302503801	●	2 - 1/2 - 4 UNC	12.402	2.000	-	2.100	1.575	1.500	6
1302502501	●	2 - 1/2 - 8 UN	10.827	1.000	5.000	2.100	1.575	1.500	6

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	○	○	○	○					○	○		
1018	1045				○	○	○	○					○	○		
50-120 SFM	45-110 SFM	40-100 SFM	45-110 SFM	20-60 SFM	30-70 SFM	30-70 SFM	20-50 SFM	40-100 SFM					20-60 SFM	15-50 SFM		

○ Good ○ Best

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

