



## List 13119

HY-PRO® AL-DIN EX-AL-SFT, DIN Overall Length

SPIRAL FLUTE	HSSE	N	3 FLUTE	C/2.5P	50°	PACKED 1 PIECE
--------------	------	---	---------	--------	-----	-------------------



EDP Number	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length
			L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)
1311900103	M3 x 0.5	D3	56.00	5.00	19.30	3.58	2.79	4.76
1311900303	M4 x 0.7	D4	63.00	5.00	21.00	4.27	3.33	6.35
1311900403	M5 x 0.8	D4	70.00	8.00	27.20	4.93	3.86	6.35
1311900503	M6 x 1	D5	80.00	10.00	28.00	6.48	4.85	7.94
1311900803	M8 x 1.25	D5	90.00	10.00	35.00	8.08	6.05	9.53
1311900903	M10 x 1.25	D5	100.00	12.00	39.00	9.68	7.26	11.11
1311901003	M10 x 1.5	D6	100.00	12.00	39.00	9.68	7.26	11.11
1311901103	M12 x 1.25	D5	100.00	14.00	49.10	9.32	6.99	11.11
1311901203	M12 x 1.5	D5	100.00	14.00	49.10	9.32	6.99	11.11
1311901303	M12 x 1.75	D6	110.00	14.00	49.10	9.32	6.99	11.11

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium					
Low	Medium	High							6061	Casting			Inconel	6Al4V	~35 HRC	35-45 HRC	45-50 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH		6061		6Al4V						
1018	1045								7075		(30 HRC)						
									40-80 SFM	40-65 SFM							

○ Good ⊙ Best

