



HY-PRO® VXL-W-OIL

Ideal for Wind Energy Applications

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

List 13127

HY-PRO® VXL-W-OIL-SFT, Vertical Applications, DIN Overall Length



EDP Number	Thread Size	Thread Limit	Overall Length		Shank Diameter	Square Width	Square Length	Number of Flutes
			L (mm)	Lc (mm)				
1312702401	M16 x 2	D7	110.00	16.00	12.19	9.14	14.29	4
1312702501	M16 x 2	D7	180.00	16.00	12.19	9.14	14.29	4
1312702301	M16 x 2	D17 (6H +0.005")	110.00	16.00	12.19	9.14	14.29	4
1312700201	M20 x 2.5	D8	200.00	19.00	16.56	12.42	17.46	4
1312700101	M20 x 2.5	D8	140.00	19.00	16.56	12.42	17.46	4
1312701601	M20 x 2.5	D18 (6H +0.005")	140.00	19.00	16.56	12.42	17.46	4
1312700401	M24 x 3	D9	160.00	24.00	19.30	14.48	19.05	5
1312700501	M24 x 3	D9	200.00	24.00	19.30	14.48	19.05	5
1312701701	M24 x 3	D19 (6H +0.005")	160.00	24.00	19.30	14.48	19.05	5
1312700701	M27 x 3	D9	200.00	24.00	22.76	17.07	22.23	5
1312700601	M27 x 3	D9	160.00	24.00	22.76	17.07	22.23	5
1312701801	M27 x 3	D19 (6H +0.005")	160.00	24.00	22.76	17.07	22.23	5
1312700801	M30 x 3.5	D10	180.00	27.00	25.93	19.46	25.40	5
1312700901	M30 x 3.5	D10	250.00	27.00	25.93	19.46	25.40	5
1312701901	M30 x 3.5	D20 (6H +0.005")	180.00	27.00	25.93	19.46	25.40	5
1312701001	M33 x 3.5	D10	180.00	27.00	28.14	21.11	26.99	5
1312701101	M33 x 3.5	D10	250.00	27.00	28.14	21.11	26.99	5
1312702001	M33 x 3.5	D20 (6H +0.005")	180.00	27.00	28.14	21.11	26.99	5
1312701201	M36 x 4	D11	199.00	32.00	31.32	23.50	28.58	5
1312701301	M36 x 4	D11	250.00	32.00	31.32	23.50	28.58	5
1312702101	M36 x 4	D21 (6H +0.005")	200.00	32.00	31.32	23.50	28.58	5
1312701401	M42 x 4.5	D11	200.00	36.00	36.32	27.23	31.75	6
1312701501	M42 x 4.5	D11	300.00	36.00	36.32	27.23	31.75	6
1312702201	M42 x 4.5	D21 (6H +0.005")	200.00	36.00	36.32	27.23	31.75	6

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium							
Low	Medium	High							6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140																
1018	1045		4340																
○	○	○	○	○	○	○	○	○					○	○					
50-120 SFM	45-110 SFM	40-100 SFM	45-110 SFM	20-60 SFM	30-70 SFM	30-70 SFM	20-50 SFM	40-100 SFM					20-60 SFM	15-50 SFM					

○ Good ○ Best

