




List 16545

A BRAND A-OIL-SFT, DIN Overall Length



EDP Number	Thread Size	Thread Limit	Overall Length			Shank Diameter	Square Width	Square Length	Number of Flutes	
			L (Inch)	Lc (Inch)	L1 (Inch)					
1654500108	●	1/4 - 20 UNC	H5	3.150	0.402	1.181	0.255	0.191	0.313	3
1654500208	●	1/4 - 28 UNF	H4	3.150	0.402	1.181	0.255	0.191	0.313	3
1654500308	●	5/16 - 18 UNC	H5	3.543	0.445	1.378	0.318	0.238	0.375	3
1654500408	●	5/16 - 24 UNF	H4	3.543	0.445	1.378	0.318	0.238	0.375	3
1654500508	●	3/8 - 16 UNC	H5	3.937	0.500	1.535	0.381	0.286	0.438	3
1654500608	●	3/8 - 24 UNF	H4	3.543	0.500	1.378	0.381	0.286	0.438	3
1654500708	●	7/16 - 14 UNC	H5	3.937	0.571	1.713	0.323	0.242	0.406	3
1654500808	●	7/16 - 20 UNF	H5	3.937	0.571	1.713	0.323	0.242	0.406	3
1654500908	●	1/2 - 13 UNC	H5	4.331	0.614	1.933	0.367	0.275	0.438	3
1654501008	●	1/2 - 20 UNF	H5	3.937	0.614	1.933	0.367	0.275	0.438	3
1654501108	●	9/16 - 12 UNC	H5	4.331	0.665	1.972	0.429	0.322	0.500	3
1654501208	●	9/16 - 18 UNF	H5	3.937	0.665	1.972	0.429	0.322	0.500	3
1654501308	●	5/8 - 11 UNC	H5	4.331	0.728	2.126	0.480	0.360	0.563	3
1654501408	●	5/8 - 18 UNF	H5	3.937	0.728	2.126	0.480	0.360	0.563	3
1654501508	●	3/4 - 10 UNC	H5	4.921	1.000	2.433	0.590	0.442	0.688	4
1654501608	●	3/4 - 16 UNF	H5	4.331	1.000	2.433	0.590	0.442	0.688	4
1654501708	●	7/8 - 9 UNC	H6	5.512	1.110	2.654	0.697	0.523	0.750	4
1654501808	●	7/8 - 14 UNF	H6	4.921	1.110	2.654	0.697	0.523	0.750	4
1654501908	●	1 - 8 UNC	H6	6.299	1.252	3.012	0.800	0.600	0.813	4
1654502008	●	1 - 8 UNC	H8	6.299	1.252	3.012	0.800	0.600	0.813	4
1654502108	●	1 - 12 UNF	H6	5.512	1.252	3.012	0.800	0.600	0.813	4
1654502208	●	1- 1/8 - 7 UNC	H9	7.087	1.732	3.819	0.896	0.672	0.875	4
1654502308	●	1- 1/8 - 8 UN	H9	7.087	1.496	3.819	0.896	0.672	0.875	4
1654502408	●	1- 1/8 - 12 UNF	H8	5.906	1.496	3.071	0.896	0.672	0.875	4
1654502508	●	1- 1/4 - 7 UNC	H10	7.087	1.732	3.937	1.021	0.766	1.000	4
1654502608	●	1- 1/4 - 8 UN	H9	7.087	1.496	3.937	1.021	0.766	1.000	4
1654502708	●	1- 1/4 - 12 UNF	H8	5.906	1.496	3.071	1.021	0.766	1.000	4
1654502808	●	1- 3/8 - 6 UNC	H10	7.874	2.008	4.528	1.108	0.831	1.063	4
1654502908	●	1- 3/8 - 8 UN	H9	7.874	1.496	4.528	1.108	0.831	1.063	4
1654503008	●	1- 3/8 - 12 UNF	H8	6.693	1.496	3.583	1.108	0.831	1.063	4
1654503108	●	1- 1/2 - 6 UNC	H10	7.874	2.008	4.528	1.233	0.925	1.125	4
1654503208	●	1- 1/2 - 8 UN	H9	7.874	1.496	4.528	1.233	0.925	1.125	4
1654503308	●	1- 1/2 - 12 UNF	H8	6.693	1.496	3.583	1.233	0.925	1.125	4
1654503408	●	1- 5/8 - 8 UN	H10	7.874	1.496	4.331	1.305	0.979	1.125	4
1654503508	●	1- 3/4 - 5 UNC	H11	8.661	2.402	4.724	1.430	1.072	1.250	4
1654503608	●	1- 3/4 - 8 UN	H10	7.874	2.008	3.976	1.430	1.072	1.250	4
1654503708	●	1- 7/8 - 8 UN	H10	8.858	2.008	4.921	1.519	1.139	1.250	4
1654503808	●	2 - 4.5 UNC	H12	9.843	2.677	5.512	1.644	1.233	1.375	4
1654503908	●	2 - 8 UN	H10	8.858	2.008	4.803	1.644	1.233	1.375	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H				
Steel					Stainless Steel				Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Low	Medium	High	Alloy Steel	Die Steel	300	400	17-4 PH			Aluminum	Nickel Alloy	Titanium	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1018	1045	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
100-200 SFM	100-200 SFM	100-200 SFM	50-100 SFM	40-80 SFM	25-70 SFM	25-70 SFM	25-50 SFM	60-150 SFM	90-220 SFM	90-220 SFM			50-100 SFM				

○ Good ○ Best

