




List 16575

A BRAND A-LT-NPT, Long Shank, NPT, Interrupted Thread

A SPIRAL FLUTE HSSE V 40° PACKED 1 PIECE



EDP	Thread Size	Overall Length			Thread Length		Shank Diameter		Square Width		Number of Flutes
		L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)				
1657501008	●	1/16 - 27 NPT	4.000	0.689	1.614	0.313	0.234	0.375	3		
1657502008	●	1/16 - 27 NPT	6.000	0.689	2.402	0.313	0.234	0.375	3		
1657503008	●	1/8 - 27 NPT	4.000	0.752	1.614	0.313	0.234	0.375	3		
1657504008	●	1/8 - 27 NPT	6.000	0.752	2.402	0.313	0.234	0.375	3		
1657505008	●	1/8 - 27 NPT	4.000	0.752	1.614	0.438	0.328	0.375	3		
1657506008	●	1/8 - 27 NPT	6.000	0.752	2.402	0.438	0.328	0.375	3		
1657507008	●	1/4 - 18 NPT	4.000	1.063	1.929	0.563	0.421	0.438	3		
1657508008	●	1/4 - 18 NPT	6.000	1.063	2.402	0.563	0.421	0.438	3		
1657509008	●	3/8 - 18 NPT	4.000	1.063	1.969	0.700	0.531	0.500	4		
1657510008	●	3/8 - 18 NPT	6.000	1.063	2.402	0.700	0.531	0.500	4		
1657511008	●	1/2 - 14 NPT	4.000	1.374	2.362	0.688	0.515	0.625	4		
1657512008	●	1/2 - 14 NPT	6.000	1.374	2.402	0.688	0.515	0.625	4		
1657513008	●	3/4 - 14 NPT	4.000	1.374	2.504	0.906	0.679	0.688	4		
1657514008	●	3/4 - 14 NPT	6.000	1.374	2.913	0.906	0.679	0.688	4		
1657515008	●	1 - 11.5 NPT	4.000	1.752	2.504	1.125	0.843	0.813	4		
1657516008	●	1 - 11.5 NPT	6.000	1.752	3.150	1.125	0.843	0.813	4		

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium							
Low	Medium	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1018	1045	1065	4340		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
5-35 SFM	5-35 SFM	5-35 SFM	5-20 SFM	5-20 SFM	5-20 SFM	5-20 SFM	5-20 SFM	5-20 SFM	5-35 SFM		5-10 SFM	5-20 SFM							

○ Good ⊗ Best

