



A Brand A-Pipe

Advanced Performance Pipe Taps

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

List 16580

A BRAND A-BSPP-RP, Made to RP Spec.



SPIRAL FLUTE	HSSE	V	40°	PACKED 1 PIECE
--------------	------	---	-----	-------------------



EDP	Thread Size	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
		L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1658001008	1/8 - 28 BSPP	3.543	0.591	1.457	0.313	0.234	0.375	3
1658002008	1/4 - 19 BSPP	3.937	0.748	1.929	0.563	0.421	0.438	3
1658003008	3/8 - 19 BSPP	3.937	0.827	1.969	0.700	0.531	0.500	4
1658004008	1/2 - 14 BSPP	4.921	1.024	2.362	0.688	0.515	0.625	4
1658005008	3/4 - 14 BSPP	5.511	1.102	2.913	0.906	0.679	0.688	4
1658006008	1 - 11 BSPP	6.299	1.299	3.150	1.125	0.843	0.813	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: A Brand A-BSPP-RP is made to a ISO-7 R(p) standards - cylindrical female with internal threads rather than ISO 228, therefore the pitch diameter tolerance of ISO-7 extends lower than that of ISO 228 which can lead to tight or non-gaging fit. Please contact our customer service department should you require assistance.



P					M			K	N		S	H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium								
Low	Medium	High			6061	Casting				Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC		
1010	1035	1065	4140	4340	300	400	17-4 PH	6061 7075									
○	○	○	○	○	○	○			○			○	○				
5-35 SFM	5-35 SFM	5-35 SFM	5-20 SFM	5-20 SFM	5-20 SFM	5-20 SFM			5-35 SFM			5-10 SFM	5-20 SFM				

○ Good ○ Best

