




## List 16640

A BRAND AT-2, Straight Flute, End Cut



EDP Number	Thread Size	Diameter		Overall Length	Length of Cut	Neck Length	Shank Diameter	Coolant-Through
		D (mm)	L (mm)	Lc (mm)	L1 (mm)	d (mm)		
8331200	●	M3 x 0.5	2.40	50.00	1.50	7.25	6.00	-
8331201	●	M4 x 0.7	3.10	50.00	2.10	9.75	6.00	-
8331202	●	M5 x 0.8	4.00	50.00	2.40	12.00	6.00	-
8331203	●	M6 x 1	4.60	50.00	3.00	14.50	6.00	-
8331204	●	M8 x 1.25	6.20	70.00	3.75	19.13	10.00	-
8331205	●	M10 x 1.5	7.50	70.00	4.50	23.75	10.00	●
8331206	●	M12 x 1.75	9.00	80.00	5.25	28.38	10.00	●

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked  
 Note: For internal threads only.



ABOUT OSG

DRILLING


THREADING

MILLING

HOLDERS

INDEX

For more information on thread mill applications, including ThreadPro software, visit: [osgtool.com/ThreadPro](http://osgtool.com/ThreadPro).



P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium								
Low	Medium	High			6061	Casting				Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC		
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075								
1018	1045																

○ Good ○ Best

