



EXOPRO® UVX-Ni

Designed for Nickel Based Alloys

List 2055

EXOPRO® UVX-Ni



SPEED FEED
1434

CARBIDE

EXO®



41-43°



STUB

REG

PACKED
1 PIECE

Cutting Diameter Tolerance	
1/4" ≤ D ≤ 1"	+0 / -0.0015"



EDP Number	Diameter	Corner Radius	Length of Cut	Overall Length	Shank Diameter	Weldon Flat
20552501	1/4	0.015	0.625	2.500	0.250	-
20552502	1/4	0.030	0.625	2.500	0.250	-
20552503	1/4	0.060	0.625	2.500	0.250	-
20553121	5/16	0.015	0.750	2.500	0.313	-
20553122	5/16	0.030	0.750	2.500	0.313	-
20553123	5/16	0.060	0.750	2.500	0.313	-
20553751	3/8	0.015	0.875	2.500	0.375	●
20553752	3/8	0.030	0.875	2.500	0.375	●
20553753	3/8	0.060	0.875	2.500	0.375	●
20555001	1/2	0.030	0.625	2.500	0.500	●
20555002	1/2	0.030	1.000	3.000	0.500	●
20555003	1/2	0.060	1.000	3.000	0.500	●
20555004	1/2	0.015	1.250	3.500	0.500	●
20555005	1/2	0.030	1.250	3.500	0.500	●
20555006	1/2	0.060	1.250	3.500	0.500	●
20555007	1/2	0.090	1.250	3.500	0.500	●
20555008	1/2	0.120	1.250	3.500	0.500	●
20556251	5/8	0.030	1.250	3.500	0.625	●
20556252	5/8	0.060	1.250	3.500	0.625	●
20556253	5/8	0.090	1.250	3.500	0.625	●
20556254	5/8	0.120	1.250	3.500	0.625	●
20557501	3/4	0.030	1.500	4.000	0.750	●
20557502	3/4	0.060	1.500	4.000	0.750	●
20557503	3/4	0.090	1.500	4.000	0.750	●
20557504	3/4	0.120	1.500	4.000	0.750	●
20551001	1	0.030	1.500	4.000	1.000	●
20551002	1	0.060	1.500	4.000	1.000	●
20551003	1	0.090	1.500	4.000	1.000	●
20551004	1	0.120	1.500	4.000	1.000	●

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

EP

P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium										
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC			
1010	1035	1045	1065	4140	4340	300	400	17-4 PH											
						○	○	○				◎				○			

○ Good ◎ Best

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

