



# HY-PRO® DIN

Premium Design for a Wide Range of Materials

ABOUT OSG

DRILLING

THREADING

MILLING


HOLDERS

INDEX

## List 260

HY-PRO® OIL-TIN-POT, DIN Overall Length

SPIRAL POINT	HSSE	TiN	C/4P	0°	PACKED 1 PIECE
--------------	------	-----	------	----	-------------------



EDP	Thread Size	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
		L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
2630005	● 1/4 - 20 UNC	3.150	0.598	1.181	0.255	0.191	0.313	3
2630405	● 1/4 - 28 UNF	3.150	0.598	1.181	0.255	0.191	0.313	3
2630805	● 5/16 - 18 UNC	3.543	0.665	1.378	0.318	0.238	0.375	3
2631205	● 5/16 - 24 UNF	3.543	0.665	1.378	0.318	0.238	0.375	3
2631605	● 3/8 - 16 UNC	3.937	0.752	1.378	0.381	0.286	0.438	3
2631805	● 3/8 - 24 UNF	3.937	0.752	1.378	0.381	0.286	0.438	3
2632005	● 7/16 - 14 UNC	3.937	0.858	1.291	0.323	0.242	0.406	3
2632205	● 7/16 - 20 UNF	3.937	0.858	1.291	0.323	0.242	0.406	3
2632405	● 1/2 - 13 UNC	4.331	0.921	1.354	0.367	0.275	0.438	3
2632605	● 1/2 - 20 UNF	3.937	0.921	1.354	0.367	0.275	0.438	3
2633005	● 9/16 - 18 UNF	3.937	1.000	1.472	0.429	0.322	0.500	3
2633205	● 5/8 - 11 UNC	4.331	1.091	1.563	0.480	0.360	0.563	3
2633405	● 5/8 - 18 UNF	3.937	1.091	1.563	0.480	0.360	0.563	3
2633605	● 3/4 - 10 UNC	4.921	1.201	1.713	0.590	0.442	0.688	3
2633805	● 3/4 - 16 UNF	4.331	1.201	1.713	0.590	0.442	0.688	3
2634005	● 7/8 - 9 UNC	5.512	1.335	1.886	0.697	0.523	0.750	3
2634205	● 7/8 - 14 UNF	4.921	1.335	1.886	0.697	0.523	0.750	3
2634405	● 1 - 8 UNC	6.299	1.500	2.091	0.800	0.600	0.813	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
○	○	⊗	⊗	⊗	○	○	○	○	○	○			○			
50-120 SFM	45-110 SFM	40-100 SFM	45-110 SFM	20-60 SFM	20-70 SFM	30-50 SFM	20-50 SFM	40-100 SFM	50-125 SFM	50-110 SFM			20-60 SFM			

○ Good ⊗ Best

