



List 2680

EXOPRO® AERO-REC, Roughing Router

SPEED FEED 1508	CARBIDE	DIA	15°			SHANK h6	REG	LONG	PACKED 1 PIECE
---------------------------	----------------	------------	------------	--	--	--------------------	------------	-------------	--------------------------

Cutting Diameter Tolerance	
1/4" ≤ D ≤ 1/2"	+0 / -0.002"



EDP Number		Diameter	Length of Cut	Overall Length	Shank Diameter	Number of Flutes
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)	
26809316	●	15/64	0.750	2.500	0.250	4
26805316	●	1/4	0.500	2.500	0.250	4
26800316	●	1/4	0.750	2.500	0.250	4
26806316	●	1/4	1.000	3.000	0.250	4
26809416	●	5/16	0.938	3.000	0.375	6
26809516	●	23/64	1.125	3.000	0.375	6
26805516	●	3/8	0.750	3.000	0.375	6
26800516	●	3/8	1.125	3.000	0.375	6
26809616	●	7/16	1.313	3.000	0.500	8
26809716	●	31/64	1.500	3.000	0.500	8
26805716	●	1/2	1.000	3.000	0.500	8
26800716	●	1/2	1.500	3.000	0.500	8

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

Carbon Fiber (CFRP)	Glass Fiber (GFRP)	Aramid Fiber (AFRP)	Honeycomb					Carbon/Carbon	Carbon Fiber/Aluminum Stack	Carbon Fiber/Titanium Stack	Carbon Fiber/Al/Ti/CRES Stack
			CFRP/Nomex	GFRP/Nomex	AFRP	CFRP/Al	Al/Al				
○	○		○	○		○	○				

○ Good ○ Best

