



List 2943

EXOCARB® AERO-ETL

SPEED FEED 1377	CARBIDE	DLC	3 FLUTE	35°			SHANK h6	REG	LONG	PACKED 1 PIECE
---------------------------	----------------	------------	----------------	------------	--	--	--------------------	------------	-------------	--------------------------

Cutting Diameter Tolerance	
12mm ≤ D ≤ 20mm	+0 / -0.020mm



EDP Number		Diameter		Corner Radius	Length of Cut	Overall Length	Shank Diameter
		D (mm)	R (mm)	R (mm)	Lc (mm)	L (mm)	d (mm)
8533350	●	12.00	-	-	50.00	110.00	12.00
8533351	●	12.00	1.00	1.00	50.00	110.00	12.00
8533352	●	12.00	1.60	1.60	50.00	110.00	12.00
8533353	●	12.00	3.00	3.00	50.00	110.00	12.00
8533354	●	12.00	4.00	4.00	50.00	110.00	12.00
8533355	●	16.00	-	-	50.00	110.00	16.00
8533356	●	16.00	1.00	1.00	50.00	110.00	16.00
8533357	●	16.00	1.60	1.60	50.00	110.00	16.00
8533358	●	16.00	3.00	3.00	50.00	110.00	16.00
8533359	●	16.00	4.00	4.00	50.00	110.00	16.00
8533360	●	16.00	5.00	5.00	50.00	110.00	16.00
8533361	●	20.00	-	-	50.00	110.00	20.00
8533362	●	20.00	1.00	1.00	50.00	110.00	20.00
8533363	●	20.00	1.60	1.60	50.00	110.00	20.00
8533364	●	20.00	3.00	3.00	50.00	110.00	20.00
8533365	●	20.00	4.00	4.00	50.00	110.00	20.00
8533366	●	20.00	5.00	5.00	50.00	110.00	20.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	4340														
1018	1045								○	○								

○ Good ○ Best

