




List 296

HY-PRO® AL-SFT

SPIRAL FLUTE	HSSE	BR	2 FLUTE	C/2P	50°	PACKED 1 PIECE
--------------	------	----	---------	------	-----	-------------------



EDP Number	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length
			L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)
2963300	M3 x 0.5	D3	49.20	4.10	16.00	3.58	2.79	4.76
2963400	M4 x 0.7	D4	54.00	5.60	19.10	4.27	3.33	6.35
2963500	M5 x 0.8	D5	60.30	6.40	22.19	4.93	3.86	6.35
2963600	M6 x 1	D5	63.50	8.00	25.40	6.48	4.85	7.94
2963800	M8 x 1.25	D5	69.10	10.00	28.60	8.08	6.05	9.53
2964000	M10 x 1.25	D5	74.60	11.98	31.80	9.68	7.26	11.11
2964100	M10 x 1.5	D6	74.60	11.98	31.80	9.68	7.26	11.11

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
Note: Other coatings are available upon request.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S	H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	Casting			6Al4V	~35 HRC	35-45 HRC	45-50 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH		6061		6Al4V					
1018	1045								7075		(30 HRC)					
									○	○						
									40-80 SFM	40-65 SFM						

○ Good ○ Best

