




List 300D

OSG CARBIDE CHUCKING REAMER



SPEED FEED	CARBIDE	BR	0°	PACKED
341				1 PIECE

Cutting Diameter Tolerance		
Size (mm)	mm	Inch
0.80mm-6.45mm	+0.025/+0.102	+0.001/+0.004
6.451mm-13mm	+0.025/+0.127	+0.001/+0.005

EDP Number		Diameter (D)					Flute Length	Overall Length	Shank Diameter	Number of Flutes
		Fractional Size	Wire Gage	Letter Size	mm	Inch				
300-0315	●	-	-	-	0.800	0.03150	0.375	1.500	0.031	4
300-0354	●	-	-	-	0.900	0.03543	0.375	1.500	0.034	4
300-0394	●	-	-	-	1.000	0.03937	0.394	1.500	0.032	4
300-0433	●	-	-	-	1.100	0.04331	0.375	1.500	0.041	4
300-0465	●	-	56	-	1.181	0.04650	0.375	1.500	0.041	4
300-0469	●	3/64	-	-	1.191	0.04688	0.375	1.500	0.041	4
300-0472	●	-	-	-	1.200	0.04724	0.375	1.500	0.041	4
300-0512	●	-	-	-	1.300	0.05118	0.375	1.500	0.041	4
300-0520	●	-	55	-	1.321	0.05200	0.375	1.500	0.041	4
300-0550	●	-	54	-	1.397	0.05500	0.375	1.500	0.052	4
300-0551	●	-	-	-	1.400	0.05510	0.394	1.500	0.053	4
300-0591	●	-	-	-	1.500	0.05906	0.375	1.500	0.052	4
300-0595	●	-	53	-	1.511	0.05950	0.375	1.500	0.052	4
300-0625	●	1/16	-	-	1.588	0.06250	0.375	1.500	0.052	4
300-0630	●	-	-	-	1.600	0.06299	0.375	1.500	0.052	4
300-0635	●	-	52	-	1.613	0.06350	0.375	1.500	0.052	4
300-0669	●	-	-	-	1.700	0.06693	0.500	1.750	0.063	4
300-0670	●	-	51	-	1.702	0.06700	0.500	1.750	0.063	4
300-0700	●	-	50	-	1.778	0.07000	0.500	1.750	0.063	4
300-0709	●	-	-	-	1.800	0.07087	0.500	1.750	0.063	4
300-0730	●	-	49	-	1.854	0.07300	0.500	1.750	0.063	4
300-0748	●	-	-	-	1.900	0.07480	0.500	1.750	0.063	4
300-0760	●	-	48	-	1.930	0.07600	0.500	1.750	0.063	4
300-0781	●	5/64	-	-	1.984	0.07813	0.500	1.750	0.063	4
300-0785	●	-	47	-	1.994	0.07850	0.500	1.750	0.063	4
300-0787	●	-	-	-	2.000	0.07874	0.500	1.750	0.063	4
300-0810	●	-	46	-	2.057	0.08100	0.500	2.000	0.078	4
300-0820	●	-	45	-	2.083	0.08200	0.500	2.000	0.078	4
300-0827	●	-	-	-	2.100	0.08268	0.500	2.000	0.078	4
300-0860	●	-	44	-	2.184	0.08600	0.500	2.000	0.078	4
300-0866	●	-	-	-	2.200	0.08661	0.500	2.000	0.078	4
300-0890	●	-	43	-	2.261	0.08900	0.500	2.000	0.078	4
300-0906	●	-	-	-	2.300	0.09055	0.500	2.000	0.078	4
300-0935	●	-	42	-	2.375	0.09350	0.500	2.000	0.078	4
300-0938	●	3/32	-	-	2.381	0.09375	0.500	2.000	0.078	4
300-0945	●	-	-	-	2.400	0.09449	0.500	2.000	0.078	4
300-0960	●	-	41	-	2.438	0.09600	0.625	2.250	0.094	4
300-0980	●	-	40	-	2.489	0.09800	0.625	2.250	0.094	4
300-0984	●	-	-	-	2.500	0.09843	0.625	2.250	0.094	4
300-0995	●	-	39	-	2.527	0.09950	0.625	2.250	0.094	4
300-1015	●	-	38	-	2.578	0.10150	0.625	2.250	0.094	4
300-1024	●	-	-	-	2.600	0.10236	0.625	2.250	0.094	4
300-1040	●	-	37	-	2.642	0.10400	0.625	2.250	0.094	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



CONTINUED

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium							
Low	Medium	High			6061	Casting				Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○		○		○	○	○	○	○							

○ Good ⊙ Best






List 300D (Continued)

OSG CARBIDE CHUCKING REAMER

SPEED FEED	CARBIDE	BR	0°	PACKED
341				1 PIECE

Cutting Diameter Tolerance		
Size (mm)	mm	Inch
0.80mm-6.45mm	+0.025/+0.0102	+0.001/+0.0004
6.451mm-13mm	+0.025/+0.0127	+0.001/+0.0005



EDP Number		Diameter (D)					Flute Length FL (mm)	Overall Length L (mm)	Shank Diameter d (mm)	Number of Flutes
		Fractional Size	Wire Gage	Letter Size	mm	Inch				
300-1063	●	-	-	-	2.700	0.10630	0.625	2.250	0.094	4
300-1065	●	-	36	-	2.705	0.10650	0.625	2.250	0.094	4
300-1094	●	7/64	-	-	2.778	0.10938	0.625	2.250	0.094	4
300-1100	●	-	35	-	2.794	0.11000	0.625	2.250	0.094	4
300-1102	●	-	-	-	2.800	0.11024	0.625	2.250	0.094	4
300-1110	●	-	34	-	2.819	0.11100	0.625	2.250	0.094	4
300-1130	●	-	33	-	2.870	0.11300	0.625	2.250	0.094	4
300-1142	●	-	-	-	2.900	0.11417	0.625	2.250	0.109	4
300-1160	●	-	32	-	2.946	0.11600	0.625	2.250	0.109	4
300-1181	●	-	-	-	3.000	0.11811	0.625	2.250	0.109	4
300-1200	●	-	31	-	3.048	0.12000	0.625	2.250	0.109	4
300-1220	●	-	-	-	3.100	0.12205	0.625	2.250	0.109	4
300-1250	●	1/8	-	-	3.175	0.12500	0.625	2.250	0.109	4
300-1260	●	-	-	-	3.200	0.12598	0.625	2.250	0.109	4
300-1285	●	-	30	-	3.264	0.12850	0.625	2.250	0.109	4
300-1299	●	-	-	-	3.300	0.12992	0.750	2.500	0.125	4
300-1339	●	-	-	-	3.400	0.13386	0.750	2.500	0.125	4
300-1360	●	-	29	-	3.454	0.13600	0.750	2.500	0.125	4
300-1378	●	-	-	-	3.500	0.13780	0.750	2.500	0.125	4
300-1405	●	-	28	-	3.569	0.14050	0.750	2.500	0.125	4
300-1406	●	9/64	-	-	3.572	0.14063	0.750	2.500	0.125	4
300-1417	●	-	-	-	3.600	0.14173	0.750	2.500	0.125	4
300-1440	●	-	27	-	3.658	0.14400	0.750	2.500	0.125	4
300-1457	●	-	-	-	3.700	0.14567	0.750	2.500	0.141	4
300-1470	●	-	26	-	3.734	0.14700	0.750	2.500	0.141	4
300-1495	●	-	25	-	3.797	0.14950	0.750	2.500	0.141	4
300-1496	●	-	-	-	3.800	0.14960	0.750	2.500	0.141	4
300-1520	●	-	24	-	3.861	0.15200	0.750	2.500	0.141	4
300-1535	●	-	-	-	3.900	0.15354	0.750	2.500	0.141	4
300-1540	●	-	23	-	3.912	0.15400	0.750	2.500	0.141	4
300-1562	●	5/32	-	-	3.969	0.15625	0.750	2.500	0.141	4
300-1570	●	-	22	-	3.988	0.15700	0.750	2.500	0.141	4
300-1575	●	-	-	-	4.000	0.15748	0.750	2.500	0.141	4
300-1590	●	-	21	-	4.039	0.15900	0.750	2.500	0.141	4
300-1610	●	-	20	-	4.089	0.16100	0.875	2.750	0.156	4
300-1614	●	-	-	-	4.100	0.16142	0.875	2.750	0.156	4
300-1654	●	-	-	-	4.200	0.16535	0.875	2.750	0.156	4
300-1660	●	-	19	-	4.216	0.16600	0.875	2.750	0.156	4
300-1693	●	-	-	-	4.300	0.16929	0.875	2.750	0.156	4
300-1695	●	-	18	-	4.305	0.16950	0.875	2.750	0.156	4
300-1719	●	11/64	-	-	4.366	0.17188	0.875	2.750	0.156	4
300-1730	●	-	17	-	4.394	0.17300	0.875	2.750	0.156	4
300-1732	●	-	-	-	4.400	0.17323	0.875	2.750	0.156	4
300-1770	●	-	16	-	4.496	0.17700	0.875	2.750	0.172	4
300-1772	●	-	-	-	4.500	0.17720	0.875	2.750	0.172	4
300-1800	●	-	15	-	4.572	0.18000	0.875	2.750	0.172	4
300-1811	●	-	-	-	4.600	0.18110	0.875	2.750	0.172	4
300-1820	●	-	14	-	4.623	0.18200	0.875	2.750	0.172	4
300-1850	●	-	13	-	4.699	0.18500	0.875	2.750	0.172	4
300-1875	●	3/16	-	-	4.763	0.18750	0.875	2.750	0.172	4
300-1890	●	-	12	-	4.801	0.18900	0.875	2.750	0.172	4
300-1910	●	-	11	-	4.851	0.19100	1.000	3.000	0.188	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX



List 300D (Continued)

OSG CARBIDE CHUCKING REAMER

SPEED FEED 341	CARBIDE	BR	0°	PACKED 1 PIECE
--------------------------	----------------	-----------	-----------	--------------------------

EDP Number		Diameter (D)					Flute Length	Overall Length	Shank Diameter	Number of Flutes
		Fractional Size	Wire Gage	Letter Size	mm	Inch	FL (mm)	L (mm)	d (mm)	
300-1929	●	-	-	-	4.900	0.19291	0.875	2.750	0.188	4
300-1935	●	-	10	-	4.915	0.19350	0.875	2.750	0.188	4
300-1960	●	-	9	-	4.978	0.19600	1.000	3.000	0.188	4
300-1969	●	-	-	-	5.000	0.19685	1.000	3.000	0.188	4
300-1990	●	-	8	-	5.055	0.19900	1.000	3.000	0.188	4
300-2008	●	-	-	-	5.100	0.20079	1.000	3.000	0.188	4
300-2010	●	-	7	-	5.105	0.20100	1.000	3.000	0.188	4
300-2031	●	13/64	-	-	5.159	0.20313	1.000	3.000	0.188	4
300-2040	●	-	6	-	5.182	0.20400	1.000	3.000	0.188	4
300-2047	●	-	-	-	5.200	0.20472	1.000	3.000	0.188	4
300-2055	●	-	5	-	5.220	0.20550	1.000	3.000	0.188	4
300-2087	●	-	-	-	5.300	0.20866	1.000	3.000	0.188	4
300-2090	●	-	4	-	5.309	0.20900	1.000	3.000	0.188	4
300-2126	●	-	-	-	5.400	0.21260	1.000	3.000	0.188	4
300-2130	●	-	3	-	5.410	0.21300	1.000	3.000	0.188	4
300-2165	●	-	-	-	5.500	0.21654	1.000	3.000	0.188	4
300-2188	●	7/32	-	-	5.556	0.21875	1.000	3.000	0.188	4
300-2205	●	-	-	-	5.600	0.22047	1.000	3.000	0.188	4
300-2210	●	-	2	-	5.613	0.22100	1.000	3.000	0.188	4
300-2244	●	-	-	-	5.700	0.22441	1.000	3.000	0.219	4
300-2280	●	-	1	-	5.791	0.22800	1.000	3.000	0.219	4
300-2283	●	-	-	-	5.800	0.22835	1.000	3.000	0.219	4
300-2323	●	-	-	-	5.900	0.23228	1.000	3.000	0.219	4
300-2340	●	-	-	A	5.944	0.23400	1.000	3.000	0.219	4
300-2344	●	15/64	-	-	5.953	0.23438	1.000	3.000	0.219	4
300-2362	●	-	-	-	6.000	0.23622	1.000	3.000	0.219	4
300-2380	●	-	-	B	6.045	0.23800	1.000	3.000	0.219	4
300-2402	●	-	-	-	6.100	0.24016	1.000	3.000	0.219	4
300-2420	●	-	-	C	6.147	0.24200	1.000	3.000	0.219	4
300-2441	●	-	-	-	6.200	0.24409	0.984	2.990	0.219	4
300-2460	●	-	-	D	6.248	0.24600	1.000	3.000	0.219	4
300-2480	●	-	-	-	6.300	0.24803	1.000	3.000	0.219	4
300-2500	●	1/4	-	E	6.350	0.25000	1.000	3.000	0.219	4
300-2520	●	-	-	-	6.400	0.25197	1.142	3.268	0.250	4
300-2559	●	-	-	-	6.500	0.25591	1.125	3.250	0.250	6
300-2570	●	-	-	F	6.528	0.25700	1.125	3.250	0.250	6
300-2598	●	-	-	-	6.600	0.25984	1.125	3.250	0.250	6
300-2610	●	-	-	G	6.629	0.26100	1.125	3.250	0.250	6
300-2638	●	-	-	-	6.700	0.26378	1.125	3.250	0.250	6
300-2656	●	17/64	-	-	6.747	0.26563	1.125	3.250	0.250	6
300-2660	●	-	-	H	6.756	0.26600	1.125	3.250	0.250	6
300-2677	●	-	-	-	6.800	0.26772	1.125	3.250	0.250	6
300-2717	●	-	-	-	6.900	0.27165	1.125	3.250	0.250	6
300-2720	●	-	-	I	6.909	0.27200	1.125	3.250	0.250	6
300-2756	●	-	-	-	7.000	0.27559	1.125	3.250	0.250	6
300-2770	●	-	-	J	7.036	0.27700	1.125	3.250	0.250	6
300-2795	●	-	-	-	7.100	0.27953	1.125	3.250	0.250	6
300-2810	●	-	-	K	7.137	0.28100	1.125	3.250	0.250	6

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



CONTINUED ➔

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	○	○	○	○	○	○						
1018	1045				○	○	○	○	○	○						

○ Good ⊗ Best






List 300D (Continued)

OSG CARBIDE CHUCKING REAMER

SPEED FEED	CARBIDE	BR	0°	PACKED
341				1 PIECE

Cutting Diameter Tolerance		
Size (mm)	mm	Inch
0.80mm-6.45mm	+0.025/+0.0102	+0.001/+0.004
6.451mm-13mm	+0.025/+0.0127	+0.001/+0.005



EDP Number		Diameter (D)					Flute Length FL (mm)	Overall Length L (mm)	Shank Diameter d (mm)	Number of Flutes
		Fractional Size	Wire Gage	Letter Size	mm	Inch				
300-2812	●	9/32	-	-	7.144	0.28125	1.125	3.250	0.250	6
300-2835	●	-	-	-	7.200	0.28346	1.125	3.250	0.250	6
300-2874	●	-	-	-	7.300	0.28740	1.125	3.250	0.281	6
300-2900	●	-	-	L	7.366	0.29000	1.125	3.250	0.281	6
300-2913	●	-	-	-	7.400	0.29134	1.125	3.250	0.281	6
300-2950	●	-	-	M	7.493	0.29500	1.125	3.250	0.281	6
300-2953	●	-	-	-	7.500	0.29528	1.125	3.250	0.281	6
300-2969	●	19/64	-	-	7.541	0.29688	1.125	3.250	0.281	6
300-2992	●	-	-	-	7.600	0.29921	1.125	3.250	0.281	6
300-3020	●	-	-	N	7.671	0.30200	1.125	3.250	0.281	6
300-3031	●	-	-	-	7.700	0.30315	1.125	3.250	0.281	6
300-3071	●	-	-	-	7.800	0.30709	1.125	3.250	0.281	6
300-3110	●	-	-	-	7.900	0.31102	1.125	3.250	0.281	6
300-3125	●	5/16	-	-	7.938	0.31250	1.125	3.250	0.281	6
300-3150	●	-	-	-	8.000	0.31496	1.125	3.250	0.281	6
300-3160	●	-	-	O	8.026	0.31600	1.250	3.500	0.313	6
300-3189	●	-	-	-	8.100	0.31890	1.250	3.500	0.313	6
300-3228	●	-	-	-	8.200	0.32283	1.250	3.500	0.313	6
300-3230	●	-	-	P	8.204	0.32300	1.250	3.500	0.313	6
300-3268	●	-	-	-	8.300	0.32677	1.250	3.500	0.313	6
300-3281	●	21/64	-	-	8.334	0.32813	1.250	3.500	0.313	6
300-3307	●	-	-	-	8.400	0.33071	1.250	3.500	0.313	6
300-3320	●	-	-	Q	8.433	0.33200	1.250	3.500	0.313	6
300-3346	●	-	-	-	8.500	0.33465	1.250	3.500	0.313	6
300-3386	●	-	-	-	8.600	0.33858	1.250	3.500	0.313	6
300-3390	●	-	-	R	8.611	0.33900	1.250	3.500	0.313	6
300-3425	●	-	-	-	8.700	0.34252	1.250	3.500	0.313	6
300-3438	●	11/32	-	-	8.733	0.34380	1.250	3.500	0.313	6
300-3465	●	-	-	-	8.800	0.34646	1.250	3.500	0.313	6
300-3480	●	-	-	S	8.839	0.34800	1.250	3.500	0.313	6
300-3504	●	-	-	-	8.900	0.35039	1.250	3.500	0.313	6
300-3543	●	-	-	-	9.000	0.35433	1.250	3.500	0.313	6
300-3580	●	-	-	T	9.093	0.35800	1.250	3.500	0.313	6
300-3583	●	-	-	-	9.100	0.35827	1.250	3.500	0.313	6
300-3594	●	23/64	-	-	9.128	0.35938	1.250	3.500	0.313	6
300-3622	●	-	-	-	9.200	0.36220	1.250	3.500	0.359	6
300-3661	●	-	-	-	9.300	0.36614	1.250	3.500	0.359	6
300-3680	●	-	-	U	9.347	0.36800	1.250	3.500	0.359	6
300-3701	●	-	-	-	9.400	0.37008	1.250	3.500	0.359	6
300-3740	●	-	-	-	9.500	0.37402	1.250	3.500	0.359	6
300-3750	●	3/8	-	-	9.525	0.37500	1.250	3.500	0.359	6
300-3770	●	-	-	V	9.576	0.37700	1.250	3.500	0.359	6
300-3780	●	-	-	-	9.600	0.37795	1.250	3.500	0.359	6
300-3819	●	-	-	-	9.700	0.38189	1.250	3.500	0.359	6
300-3858	●	-	-	-	9.800	0.38583	1.250	3.500	0.359	6
300-3860	●	-	-	W	9.804	0.38600	1.250	3.500	0.359	6
300-3898	●	-	-	-	9.900	0.38976	1.250	3.500	0.375	6
300-3906	●	25/64	-	-	9.922	0.39063	1.250	3.500	0.375	6
300-3937	●	-	-	-	10.000	0.39370	1.250	3.500	0.375	6
300-3970	●	-	-	X	10.084	0.39700	1.250	3.500	0.375	6
300-3976	●	-	-	-	10.100	0.39764	1.250	3.500	0.375	6
300-4016	●	-	-	-	10.200	0.40157	1.250	3.500	0.375	6

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX



List 300D (Continued)

OSG CARBIDE CHUCKING REAMER

SPEED FEED 341	CARBIDE	BR	0°	PACKED 1 PIECE
-------------------	---------	----	----	-------------------

EDP Number		Diameter (D)					Flute Length	Overall Length	Shank Diameter	Number of Flutes
		Fractional Size	Wire Gage	Letter Size	mm	Inch	FL (mm)	L (mm)	d (mm)	
300-4040	●	-	-	Y	10.262	0.40400	1.250	3.500	0.375	6
300-4055	●	-	-	-	10.300	0.40551	1.250	3.500	0.375	6
300-4062	●	13/32	-	-	10.319	0.40625	1.250	3.500	0.375	6
300-4094	●	-	-	-	10.400	0.40945	1.250	3.500	0.375	6
300-4130	●	-	-	Z	10.490	0.41300	1.250	3.500	0.375	6
300-4134	●	-	-	-	10.500	0.41339	1.250	3.500	0.375	6
300-4173	●	-	-	-	10.600	0.41732	1.375	3.750	0.375	6
300-4213	●	-	-	-	10.700	0.42126	1.375	3.750	0.375	6
300-4219	●	27/64	-	-	10.716	0.42188	1.375	3.750	0.375	6
300-4252	●	-	-	-	10.800	0.42520	1.375	3.750	0.375	6
300-4291	●	-	-	-	10.900	0.42913	1.375	3.750	0.375	6
300-4331	●	-	-	-	11.000	0.43307	1.378	3.750	0.375	6
300-4370	●	-	-	-	11.100	0.43701	1.375	3.750	0.375	6
300-4375	●	7/16	-	-	11.113	0.43750	1.375	3.750	0.375	6
300-4409	●	-	-	-	11.200	0.44094	1.375	3.750	0.375	6
300-4449	●	-	-	-	11.300	0.44488	1.375	3.750	0.375	6
300-4488	●	-	-	-	11.400	0.44882	1.375	3.750	0.375	6
300-4528	●	-	-	-	11.500	0.45276	1.375	3.750	0.375	6
300-4531	●	29/64	-	-	11.509	0.45313	1.375	3.750	0.438	6
300-4567	●	-	-	-	11.600	0.45669	1.375	3.750	0.438	6
300-4606	●	-	-	-	11.700	0.46063	1.375	3.750	0.438	6
300-4646	●	-	-	-	11.800	0.46457	1.375	3.750	0.438	6
300-4685	●	-	-	-	11.900	0.46850	1.375	3.750	0.438	6
300-4688	●	15/32	-	-	11.906	0.46875	1.375	3.750	0.438	6
300-4724	●	-	-	-	12.000	0.47244	1.375	3.750	0.438	6
300-4764	●	-	-	-	12.100	0.47638	1.500	4.000	0.438	6
300-4803	●	-	-	-	12.200	0.48031	1.500	4.000	0.438	6
300-4843	●	-	-	-	12.300	0.48425	1.500	4.000	0.438	6
300-4844	●	31/64	-	-	12.303	0.48438	1.500	4.000	0.438	6
300-4882	●	-	-	-	12.400	0.48819	1.500	4.000	0.438	6
300-4921	●	-	-	-	12.500	0.49213	1.500	4.000	0.438	6
300-4961	●	-	-	-	12.600	0.49606	1.500	4.000	0.438	6
300-5000	●	1/2	-	-	12.700	0.50000	1.500	4.000	0.438	6
300-5079	●	-	-	-	12.900	0.50787	1.500	4.000	0.438	6
300-5118	●	-	-	-	13.000	0.51181	1.500	4.000	0.438	6

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium							
Low	Medium	High			6061	Casting				Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	300	400	17-4 PH	7075								
○	○		○		○	○	○	○	○							

○ Good ⊙ Best

