



List 335Ni

EXOPRO® WHR-Ni-SFT, DIN Overall Length



SPIRAL FLUTE	VC10	HR	C/2.5P	11°	PACKED 1 PIECE
--------------	------	----	--------	-----	-------------------



EDP Number	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)		
3350002562	●	No. 2 - 56 UNC	H2	1.772	0.437	-	0.141	0.110	0.188	2
3350004402	●	No. 4 - 40 UNC	H2	2.205	0.563	-	0.141	0.110	0.188	3
3350004403	●	No. 4 - 40 UNC	H3	2.205	0.563	-	0.141	0.110	0.188	3
3350006322	●	No. 6 - 32 UNC	H2	2.205	0.689	-	0.141	0.110	0.188	3
3350006323	●	No. 6 - 32 UNC	H3	2.205	0.689	-	0.141	0.110	0.188	3
3350008322	●	No. 8 - 32 UNC	H2	2.480	0.748	-	0.168	0.131	0.250	3
3350008323	●	No. 8 - 32 UNC	H3	2.480	0.748	-	0.168	0.131	0.250	3
3350010243	●	No. 10 - 24 UNC	H3	2.756	0.874	-	0.194	0.152	0.250	3
3350010245	●	No. 10 - 24 UNC	H5	2.756	0.874	-	0.194	0.152	0.250	3
3350010322	●	No. 10 - 32 UNF	H2	2.756	0.866	-	0.194	0.152	0.250	3
3350010323	●	No. 10 - 32 UNF	H3	2.756	0.866	-	0.194	0.152	0.250	3
3350014203	●	1/4 - 20 UNC	H3	3.150	1.000	-	0.255	0.191	0.313	3
3350014205	●	1/4 - 20 UNC	H5	3.150	1.000	-	0.255	0.191	0.313	3
3350014283	●	1/4 - 28 UNF	H3	3.150	0.992	-	0.255	0.191	0.313	3
3350014284	●	1/4 - 28 UNF	H4	3.150	0.992	-	0.255	0.191	0.313	3
3350516183	●	5/16 - 18 UNC	H3	3.543	0.665	1.378	0.318	0.238	0.375	3
3350516185	●	5/16 - 18 UNC	H5	3.543	0.665	1.378	0.318	0.238	0.375	3
3350516243	●	5/16 - 24 UNF	H3	3.543	0.665	1.378	0.318	0.238	0.375	3
3350516245	●	5/16 - 24 UNF	H5	3.543	0.665	1.378	0.318	0.238	0.375	3
3350038163	●	3/8 - 16 UNC	H3	3.937	0.752	1.535	0.381	0.286	0.438	3
3350038165	●	3/8 - 16 UNC	H5	3.937	0.752	1.535	0.381	0.286	0.438	3
3350038243	●	3/8 - 24 UNF	H3	3.543	0.752	1.378	0.381	0.286	0.438	3
3350038244	●	3/8 - 24 UNF	H4	3.543	0.752	1.378	0.381	0.286	0.438	3
3350716143	●	7/16 - 14 UNC	H3	3.937	0.858	1.713	0.323	0.242	0.406	3
3350716145	●	7/16 - 14 UNC	H5	3.937	0.858	1.713	0.323	0.242	0.406	3
3350716203	●	7/16 - 20 UNF	H3	3.937	0.858	1.713	0.323	0.242	0.406	3
3350716205	●	7/16 - 20 UNF	H5	3.937	0.858	1.713	0.323	0.242	0.406	3
3350012133	●	1/2 - 13 UNC	H3	4.331	0.921	1.933	0.367	0.275	0.438	3
3350012135	●	1/2 - 13 UNC	H5	4.331	0.921	1.933	0.367	0.275	0.438	3
3350012203	●	1/2 - 20 UNF	H3	3.937	0.921	1.933	0.367	0.275	0.438	3
3350012205	●	1/2 - 20 UNF	H5	3.937	0.921	1.933	0.367	0.275	0.438	3
3350096183	●	9/16 - 18 UNF	H3	3.937	1.000	1.972	0.429	0.322	0.500	4
3350096185	●	9/16 - 18 UNF	H5	3.937	1.000	1.972	0.429	0.322	0.500	4
3350058113	●	5/8 - 11 UNC	H3	4.331	1.091	2.126	0.480	0.360	0.563	4
3350058115	●	5/8 - 11 UNC	H5	4.331	1.091	2.126	0.480	0.360	0.563	4
3350058183	●	5/8 - 18 UNF	H3	3.937	1.091	2.126	0.480	0.360	0.563	4
3350058185	●	5/8 - 18 UNF	H5	3.937	1.091	2.126	0.480	0.360	0.563	4
3350034103	●	3/4 - 10 UNC	H3	4.921	1.201	2.433	0.590	0.442	0.688	4
3350034105	●	3/4 - 10 UNC	H5	4.921	1.201	2.433	0.590	0.442	0.688	4
3350034163	●	3/4 - 16 UNF	H3	4.331	1.201	2.433	0.590	0.442	0.688	4
3350034165	●	3/4 - 16 UNF	H5	4.331	1.201	2.433	0.590	0.442	0.688	4
3350078093	●	7/8 - 9 UNC	H3	5.512	1.335	2.654	0.697	0.523	0.750	4
3350078095	●	7/8 - 9 UNC	H5	5.512	1.335	2.654	0.697	0.523	0.750	4
3350078143	●	7/8 - 14 UNF	H3	4.921	1.335	2.654	0.697	0.523	0.750	4
3350078145	●	7/8 - 14 UNF	H5	4.921	1.335	2.654	0.697	0.523	0.750	4
3350001083	●	1 - 8 UNC	H3	6.299	1.500	3.012	0.800	0.600	0.813	4
3350001085	●	1 - 8 UNC	H5	6.299	1.500	3.012	0.800	0.600	0.813	4
3350001123	●	1 - 12 UNF	H3	5.512	1.500	3.012	0.800	0.600	0.813	4
3350001125	●	1 - 12 UNF	H5	5.512	1.500	3.012	0.800	0.600	0.813	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H				
Steel					Stainless Steel				Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel						Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			4140 4340		300		400	17-4 PH	6061 7075			Casting	Inconel	6Al4V (30 HRC)	~35 HRC
1010 1018	1035 1045	1065										○					
							8-20 SFM			8-15 SFM					8-12 SFM		

○ Good ⊗ Best

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

