



List 337Ni

EXOPRO® WHR-Ni-POT, DIN Overall Length



SPIRAL POINT	VC10	HR	C/SP	0°	PACKED 1 PIECE
--------------	------	----	------	----	-------------------



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)		
3370002562	●	No. 2 - 56 UNC	H2	1.772	0.437	0.476	0.141	0.110	0.188	2
3370004402	●	No. 4 - 40 UNC	H2	2.205	0.562	0.602	0.141	0.110	0.188	3
3370004403	●	No. 4 - 40 UNC	H3	2.205	0.562	0.602	0.141	0.110	0.188	3
3370004482	●	No. 4 - 48 UNF	H2	2.205	0.562	0.602	0.141	0.110	0.188	3
3370006322	●	No. 6 - 32 UNC	H2	2.205	0.688	-	0.141	0.110	0.188	3
3370006323	●	No. 6 - 32 UNC	H3	2.205	0.688	-	0.141	0.110	0.188	3
3370008322	●	No. 8 - 32 UNC	H2	2.480	0.751	-	0.168	0.131	0.250	3
3370008323	●	No. 8 - 32 UNC	H3	2.480	0.751	-	0.168	0.131	0.250	3
3370010242	●	No. 10 - 24 UNC	H2	2.756	0.874	-	0.194	0.152	0.250	3
3370010243	●	No. 10 - 24 UNC	H3	2.756	0.874	-	0.194	0.152	0.250	3
3370010322	●	No. 10 - 32 UNF	H2	2.756	0.870	-	0.194	0.152	0.250	3
3370010323	●	No. 10 - 32 UNF	H3	2.756	0.870	-	0.194	0.152	0.250	3
3370014203	●	1/4 - 20 UNC	H3	3.150	1.000	-	0.255	0.191	0.313	3
3370014205	●	1/4 - 20 UNC	H5	3.150	1.000	-	0.255	0.191	0.313	3
3370014283	●	1/4 - 28 UNF	H3	3.150	0.992	-	0.255	0.191	0.313	3
3370014284	●	1/4 - 28 UNF	H4	3.150	0.992	-	0.255	0.191	0.313	3
3370516183	●	5/16 - 18 UNC	H3	3.543	0.665	1.377	0.318	0.238	0.375	3
3370516185	●	5/16 - 18 UNC	H5	3.543	0.665	1.377	0.318	0.238	0.375	3
3370516243	●	5/16 - 24 UNF	H3	3.543	0.657	1.370	0.318	0.238	0.375	3
3370516245	●	5/16 - 24 UNF	H5	3.543	0.657	1.370	0.318	0.238	0.375	3
3370038163	●	3/8 - 16 UNC	H3	3.937	0.751	1.535	0.381	0.286	0.438	3
3370038165	●	3/8 - 16 UNC	H5	3.937	0.751	1.535	0.381	0.286	0.438	3
3370038243	●	3/8 - 24 UNF	H3	3.543	0.740	1.377	0.381	0.286	0.438	3
3370038245	●	3/8 - 24 UNF	H5	3.543	0.740	1.377	0.381	0.286	0.438	3
3370716143	●	7/16 - 14 UNC	H3	3.937	0.858	1.291	0.323	0.242	0.406	3
3370716145	●	7/16 - 14 UNC	H5	3.937	0.858	1.291	0.323	0.242	0.406	3
3370716203	●	7/16 - 20 UNF	H3	3.937	0.858	1.291	0.323	0.242	0.406	3
3370716205	●	7/16 - 20 UNF	H5	3.937	0.858	1.291	0.323	0.242	0.406	3
3370012133	●	1/2 - 13 UNC	H3	4.331	0.921	1.354	0.367	0.275	0.438	3
3370012135	●	1/2 - 13 UNC	H5	4.331	0.921	1.354	0.367	0.275	0.438	3
3370012203	●	1/2 - 20 UNF	H3	3.937	0.921	1.354	0.367	0.275	0.438	3
3370012205	●	1/2 - 20 UNF	H5	3.937	0.921	1.354	0.367	0.275	0.438	3
3370916183	●	9/16 - 18 UNF	H3	3.937	1.000	1.472	0.429	0.322	0.500	3
3370916185	●	9/16 - 18 UNF	H5	3.937	1.000	1.472	0.429	0.322	0.500	3
3370058113	●	5/8 - 11 UNC	H3	4.331	1.090	1.562	0.480	0.360	0.563	3
3370058115	●	5/8 - 11 UNC	H5	4.331	1.090	1.562	0.480	0.360	0.563	3
3370058183	●	5/8 - 18 UNF	H3	3.937	1.090	1.562	0.480	0.360	0.563	3
3370058185	●	5/8 - 18 UNF	H5	3.937	1.090	1.562	0.480	0.360	0.563	3
3370034103	●	3/4 - 10 UNC	H3	4.921	1.200	1.712	0.590	0.442	0.688	4
3370034105	●	3/4 - 10 UNC	H5	4.921	1.200	1.712	0.590	0.442	0.688	4
3370034163	●	3/4 - 16 UNF	H3	4.331	1.200	1.712	0.590	0.442	0.688	4
3370034165	●	3/4 - 16 UNF	H5	4.331	1.200	1.712	0.590	0.442	0.688	4
3370078093	●	7/8 - 9 UNC	H3	5.512	1.334	1.885	0.697	0.523	0.750	4
3370078095	●	7/8 - 9 UNC	H5	5.512	1.334	1.885	0.697	0.523	0.750	4
3370078143	●	7/8 - 14 UNF	H3	4.921	1.334	1.885	0.697	0.523	0.750	4
3370078145	●	7/8 - 14 UNF	H5	4.921	1.334	1.885	0.697	0.523	0.750	4
3370001083	●	1 - 8 UNC	H3	6.299	1.500	2.090	0.800	0.600	0.813	4
3370001085	●	1 - 8 UNC	H5	6.299	1.500	2.090	0.800	0.600	0.813	4
3370001123	●	1 - 12 UNF	H3	5.512	1.500	2.090	0.800	0.600	0.813	4
3370001125	●	1 - 12 UNF	H5	5.512	1.500	2.090	0.800	0.600	0.813	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH											
1018	1045						○					⊗					○	
							8-20 SFM					8-15 SFM						8-12 SFM

○ Good ⊗ Best



ABOUT OSG
DRILLING
THREADING
MILLING
HOLDERS
INDEX