



List 3610

EXOCARB® WXL-EBD



SPEED FEED
1475

CARBIDE
WXL

2 FLUTE


30°

SHANK
h6

STUB

PACKED
1 PIECE

Radius Tolerance	
1/32" ≤ D ≤ 3/16"	+/- 0.0002"
1/4" ≤ D ≤ 3/8"	+0.0001 / -0.0003
D = 1/2"	+/- 0.0004"



EDP Number	Diameter	Length of Cut	Overall Length	Shank Diameter
36100111	1/32	0.031	2.500	0.250
36100211	1/16	0.063	2.500	0.250
36100311	3/32	0.094	2.500	0.250
36100411	1/8	0.125	3.000	0.250
36101011	5/32	0.156	2.500	0.250
36100511	3/16	0.188	3.000	0.250
36100611	1/4	0.250	3.000	0.250
36100711	5/16	0.313	4.000	0.313
36100811	3/8	0.375	4.000	0.375
36100911	1/2	0.500	4.000	0.500

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

HTE

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel						
Low	Medium	High							6061	7075			Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1018	1045	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

