



## List 3723

EXOCARB® WXL®-4D-DE



SPEED FEED  
1362-1363

CARBIDE

WXL

2 FLUTE

40°



SHANK  
h6

LONG

PACKED  
1 PIECE

Cutting Diameter Tolerance	
0.1mm ≤ D ≤ 12mm	+0 / -0.020mm



EDP Number		Diameter	Length of Cut	Overall Length	Shank Diameter
		D (mm)	Lc (mm)	L (mm)	d (mm)
3182602	●	0.20	0.80	45.00	4.00
3182603	●	0.30	1.20	45.00	4.00
3182604	●	0.40	1.60	45.00	4.00
3182605	●	0.50	2.00	45.00	4.00
3182606	●	0.60	2.40	45.00	4.00
3182607	●	0.70	2.80	45.00	4.00
3182608	●	0.80	3.20	45.00	4.00
3182609	●	0.90	3.60	45.00	4.00
3182610	●	1.00	4.00	45.00	4.00
3182611	●	1.10	4.40	45.00	4.00
3182612	●	1.20	4.80	45.00	4.00
3182613	●	1.30	5.20	45.00	4.00
3182614	●	1.40	5.60	45.00	4.00
3182615	●	1.50	6.00	45.00	4.00
3182616	●	1.60	6.40	45.00	4.00
3182617	●	1.70	6.80	45.00	4.00
3182618	●	1.80	7.20	45.00	4.00
3182619	●	1.90	7.60	45.00	4.00
3182620	●	2.00	8.00	45.00	4.00
3182621	●	2.10	8.40	45.00	4.00
3182622	●	2.20	8.80	45.00	4.00
3182623	●	2.30	9.20	45.00	4.00
3182624	●	2.40	9.60	45.00	4.00
3182625	●	2.50	10.00	45.00	4.00
3182626	●	2.60	10.40	50.00	4.00
3182627	●	2.70	10.80	50.00	4.00
3182628	●	2.80	11.20	50.00	4.00
3182629	●	2.90	11.60	50.00	4.00
3182630	●	3.00	12.00	50.00	6.00
3182631	●	3.10	12.40	50.00	6.00
3182632	●	3.20	12.80	50.00	6.00

EDP Number		Diameter	Length of Cut	Overall Length	Shank Diameter
		D (mm)	Lc (mm)	L (mm)	d (mm)
3182633	●	3.30	13.20	50.00	6.00
3182634	●	3.40	13.60	50.00	6.00
3182635	●	3.50	14.00	50.00	6.00
3182636	●	3.60	14.40	50.00	6.00
3182637	●	3.70	14.80	50.00	6.00
3182638	●	3.80	15.20	50.00	6.00
3182639	●	3.90	15.60	50.00	6.00
3182640	●	4.00	16.00	55.00	6.00
3182641	●	4.10	16.40	55.00	6.00
3182642	●	4.20	16.80	55.00	6.00
3182643	●	4.30	17.20	55.00	6.00
3182644	●	4.40	17.60	55.00	6.00
3182645	●	4.50	18.00	55.00	6.00
3182646	●	4.60	18.40	55.00	6.00
3182647	●	4.70	18.80	55.00	6.00
3182648	●	4.80	19.20	55.00	6.00
3182649	●	4.90	19.60	55.00	6.00
3182650	●	5.00	20.00	60.00	6.00
3182651	●	5.10	20.40	60.00	6.00
3182652	●	5.20	20.80	60.00	6.00
3182653	●	5.30	21.20	60.00	6.00
3182654	●	5.40	21.60	60.00	6.00
3182655	●	5.50	22.00	65.00	6.00
3182656	●	5.60	22.40	65.00	6.00
3182657	●	5.70	22.80	65.00	6.00
3182658	●	5.80	23.20	65.00	6.00
3182659	●	5.90	23.60	65.00	6.00
3182660	●	6.00	24.00	65.00	6.00
3182680	●	8.00	32.00	80.00	8.00
3182700	●	10.00	40.00	90.00	10.00
3182720	●	12.00	48.00	100.00	12.00

● Stocked ○ Available Upon Request; MOQ May Apply  
▲ Globally Stocked



● Stocked ○ Available Upon Request; MOQ May Apply  
▲ Globally Stocked



P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium							
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1018	1045	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

