



# EXOTAP VA-3<sup>®</sup> LS

Ideal for Stainless Steel

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

## List 397

EXOTAP VA-3<sup>®</sup> LS-POT, Long Shank

SPIRAL POINT	HSSE	S/O	C/4P	0°	PACKED 1 PIECE
--------------	------	-----	------	----	-------------------



EDP		Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
				L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1764001	●	No. 4 - 40 UNC	H2	4.000	0.295	0.839	0.141	0.110	0.188	2
1766201	●	No. 4 - 40 UNC	H2	6.000	0.295	0.839	0.141	0.110	0.188	2
1764101	●	No. 6 - 32 UNC	H3	4.000	0.370	1.039	0.141	0.110	0.188	2
1764201	●	No. 6 - 32 UNC	H3	6.000	0.370	1.028	0.141	0.110	0.188	2
1764301	●	No. 8 - 32 UNC	H3	4.000	0.374	1.126	0.168	0.131	0.250	3
1764401	●	No. 8 - 32 UNC	H3	6.000	0.374	1.126	0.168	0.131	0.250	3
1764501	●	No. 10 - 24 UNC	H3	4.000	0.492	1.303	0.194	0.152	0.250	3
1764601	●	No. 10 - 24 UNC	H3	6.000	0.492	1.303	0.194	0.152	0.250	3
1764701	●	No. 10 - 32 UNF	H3	4.000	0.492	1.303	0.194	0.152	0.250	3
1764801	●	No. 10 - 32 UNF	H3	6.000	0.492	1.303	0.194	0.152	0.250	3
1764901	●	1/4 - 20 UNC	H3	4.000	0.594	1.496	0.255	0.191	0.313	3
1765001	●	1/4 - 20 UNC	H3	6.000	0.594	1.496	0.255	0.191	0.313	3
1765101	●	1/4 - 28 UNF	H3	6.000	0.594	1.496	0.255	0.191	0.313	3
1765201	●	5/16 - 18 UNC	H3	6.000	0.665	1.689	0.318	0.238	0.375	3
1765701	●	5/16 - 24 UNF	H3	6.000	0.665	1.689	0.318	0.238	0.375	3
1765301	●	3/8 - 16 UNC	H3	6.000	0.752	1.874	0.381	0.286	0.438	3
1765801	●	3/8 - 24 UNF	H3	6.000	0.752	1.874	0.381	0.286	0.438	3
1765401	●	7/16 - 14 UNC	H3	6.000	0.858	1.291	0.323	0.242	0.406	3
1765901	●	7/16 - 20 UNF	H3	6.000	0.858	1.291	0.323	0.242	0.406	3
1765501	●	1/2 - 13 UNC	H3	6.000	0.921	1.354	0.367	0.275	0.438	3
1766001	●	1/2 - 20 UNF	H3	6.000	0.921	1.354	0.367	0.275	0.438	3
1765601	●	5/8 - 11 UNC	H3	6.000	1.091	1.563	0.480	0.360	0.563	3

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked  
 Note: Neck length is designed for reaching 50% deeper holes than ANSI standard taps.



P					M			K Cast Iron	N		S		H			
Steel					Stainless Steel				Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			4140 4340		300		400	17-4 PH			6061	Casting	Inconel	6Al4V (30 HRC)
1010 1018	1035 1045	1065	6061 7075													
○	○	○			○	○	○									
25-80 SFM	20-50 SFM	20-45 SFM			20-45 SFM	20-45 SFM	8-20 SFM									

○ Good ○ Best

