




## List 410

OSG COBALT HSS ROUGHER SQ

<b>SPEED FEED</b> 1422	<b>HSS-Co</b>	<b>BR</b>	<b>ROUGH</b>	<b>3 FLUTE</b>	<b>25°</b>	<b>WELDON FLAT</b>	<b>STUB</b>	<b>PACKED</b> 1 PIECE
---------------------------	---------------	-----------	--------------	----------------	------------	--------------------	-------------	--------------------------



EDP Number		Diameter		Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)	
4105200	●	1/2	0.500	2.500	0.500	
4105300	●	5/8	0.625	2.750	0.625	
4105400	●	3/4	0.750	2.875	0.750	
4105700	●	1	1.000	3.500	1.000	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked  
 Note: Other coatings available upon request.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium	Hardened Steel							
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	300	400	17-4 PH		6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	○	○	○	○	○	○	○	○	○			○	○			

○ Good ⊙ Best

