


## List 447

OSG STANDARD CARBIDE LHS/RHC

<b>SPEED FEED</b> 1406-1407	<b>CARBIDE</b>	<b>BR</b>	<b>TiAIN</b>	<b>4 FLUTE</b>	<b>30°</b>		<b>LH</b>	<b>STUB</b>	<b>REG</b>	<b>LONG</b>	<b>PACKED</b> 1 PIECE
--------------------------------	----------------	-----------	--------------	----------------	------------	--	-----------	-------------	------------	-------------	--------------------------

Cutting Diameter Tolerance	
1/16" ≤ D ≤ 1"	+0 / -0.002"



EDP Number		Diameter	Length of Cut	Overall Length	Shank Diameter	Surface Treatment
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)	
447-0625	●	1/16	0.188	1.500	0.125	BRIGHT
447-1250	●	1/8	0.500	1.500	0.125	BRIGHT
447-125011	●	1/8	0.500	1.500	0.125	TiAIN
447-1875	●	3/16	0.625	2.000	0.188	BRIGHT
447-187511	●	3/16	0.625	2.000	0.188	TiAIN
447-2500	●	1/4	0.750	2.500	0.250	BRIGHT
447-250011	●	1/4	0.750	2.500	0.250	TiAIN
447-3125	●	5/16	0.813	2.500	0.313	BRIGHT
447-3750	●	3/8	1.000	2.500	0.375	BRIGHT
447-5000	●	1/2	1.000	3.000	0.500	BRIGHT
447-6250	●	5/8	1.250	3.500	0.625	BRIGHT
447-7500	●	3/4	1.500	4.000	0.750	BRIGHT
447-1000	●	1	1.500	4.000	1.000	BRIGHT

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked  
 Note: Other coatings available upon request.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel			
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	6061	7075										
○	○	○	○	○	○	○		○	○			○	○	○		

○ Good ⊗ Best

