




List 52502

OSG PHOENIX® P2D, Flat Shank

SPEED FEED	INSERTS	ACCS.	STEEL	2 FLUTE	PACKED
362	282-283	284			1 PIECE



EDP Number	Designation	Diameter	Drilling Depth	Overall Length	Shank Diameter	Shank Length	Applicable Insert
		D (in)	L1 (in)	L (in)	d (in)	L2 (in)	
52502063	P2D0484FS075A03	0.484	0.969	3.449	0.750	1.969	XCMT03
52502064	P2D0500FS075A03	0.500	1.000	3.480	0.750	1.969	XCMT03
52502065	P2D0516FS075A03	0.516	1.031	3.512	0.750	1.969	XCMT03
52502066	P2D0531FS075A03	0.531	1.063	3.543	0.750	1.969	XCMT03
52502067	P2D0547FS075A03	0.547	1.094	3.574	0.750	1.969	XCMT03
52502068	P2D0563FS075A03	0.563	1.125	3.605	0.750	1.969	XCMT03
52502069	P2D0578FS075A03	0.578	1.156	3.637	0.750	1.969	XCMT03
52502026	P2D0594FS075A04	0.594	1.188	3.747	0.750	1.969	XCMT04
52502028	P2D0641FS075A04	0.605	1.281	3.841	0.750	1.969	XCMT04
52502027	P2D0609FS075A04	0.609	1.219	3.777	0.750	1.969	XCMT04
52502008	P2D0625FS075A04	0.625	1.250	3.809	0.750	1.969	XCMT04
52502009	P2D0656FS075A04	0.656	1.313	3.871	0.750	1.969	XCMT04
52502029	P2D0672FS075A05	0.672	1.344	4.021	0.750	1.969	XCMT05
52502010	P2D0688FS075A05	0.688	1.375	4.053	0.750	1.969	XCMT05
52502030	P2D0703FS075A05	0.703	1.406	4.883	0.750	1.969	XCMT05
52502031	P2D0719FS100A05	0.719	1.438	4.352	1.000	2.205	XCMT05
52502032	P2D0734FS100A05	0.734	1.469	4.381	1.000	2.205	XCMT05
52502011	P2D0750FS100A06	0.750	1.500	4.413	1.000	2.205	XCMT06
52502033	P2D0766FS100A06	0.766	1.531	4.445	1.000	2.205	XCMT06
52502034	P2D0781FS100A06	0.781	1.563	4.475	1.000	2.205	XCMT06
52502035	P2D0797FS100A06	0.797	1.594	4.507	1.000	2.205	XCMT06
52502012	P2D0812FS100A06	0.813	1.625	4.537	1.000	2.205	XCMT06
52502036	P2D0828FS100A07	0.828	1.656	4.766	1.000	2.205	XCMT07
52502037	P2D0844FS100A07	0.844	1.688	4.798	1.000	2.205	XCMT07
52502038	P2D0859FS100A07	0.859	1.719	4.828	1.000	2.205	XCMT07
52502000	P2D0875FS100A07	0.875	1.750	4.860	1.000	2.205	XCMT07
52502039	P2D0891FS100A07	0.891	1.781	4.892	1.000	2.205	XCMT07
52502040	P2D0906FS100A07	0.906	1.813	4.992	1.000	2.205	XCMT07
52502041	P2D0922FS100A07	0.922	1.844	4.954	1.000	2.205	XCMT07
52502001	P2D0937FS125A07	0.938	1.875	5.142	1.250	2.362	XCMT07
52502042	P2D0953FS125A07	0.953	1.906	5.174	1.250	2.362	XCMT07
52502043	P2D0969FS125A07	0.969	1.938	5.206	1.250	2.362	XCMT07
52502044	P2D0984FS125A08	0.984	1.969	5.236	1.250	2.362	XCMT08
52502002	P2D1000FS125A08	1.000	2.000	5.268	1.250	2.362	XCMT08
52502045	P2D1031FS125A08	1.031	2.063	5.330	1.250	2.362	XCMT08

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



DESIGNATION EXPLANATION

P2D-0484-FS-075-A-03



See Full Detail on Page 360

CONTINUED ➔

P	M	K	N	S	H
Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
○	○	○	○	○	○

Material recommendation based on inserts compatible with this tool body.

○ Good ○ Best






List 52502 (Continued)

OSG PHOENIX® P2D, Flat Shank

SPEED FEED	INSERTS	ACCS.	STEEL	2 FLUTE	PACKED
362	282-283	284			1 PIECE



EDP Number	Designation	Diameter	Drilling Depth	Overall Length	Shank Diameter	Shank Length	Applicable Insert	
		D (in)	l1 (in)	L (in)	d (in)	l2 (in)		
52502003	●	P2D1062FS125A08	1.063	2.125	5.392	1.250	2.362	XCMT08
52502046	●	P2D1094FS125A08	1.094	2.188	5.456	1.250	2.362	XCMT08
52502004	●	P2D1125FS125A08	1.125	2.250	5.518	1.250	2.362	XCMT08
52502047	●	P2D1156FS125A09	1.156	2.313	5.580	1.250	2.362	XCMT09
52502005	●	P2D1187FS125A09	1.188	2.375	5.642	1.250	2.362	XCMT09
52502048	●	P2D1219FS125A09	1.219	2.438	5.706	1.250	2.362	XCMT09
52502006	●	P2D1250FS125A09	1.250	2.500	5.768	1.250	2.362	XCMT09
52502049	●	P2D1281FS150A09	1.281	2.563	6.223	1.500	2.756	XCMT09
52502007	●	P2D1312FS150A09	1.313	2.625	6.285	1.500	2.756	XCMT09
52502050	●	P2D1344FS150A10	1.344	2.688	6.350	1.500	2.756	XCMT10
52502013	●	P2D1375FS150A10	1.375	2.750	6.411	1.500	2.756	XCMT10
52502051	●	P2D1406FS150A10	1.406	2.813	6.473	1.500	2.756	XCMT10
52502014	●	P2D1437FS150A10	1.438	2.875	6.535	1.500	2.756	XCMT10
52502052	●	P2D1469FS150A10	1.469	2.938	6.600	1.500	2.756	XCMT10
52502015	●	P2D1500FS150A10	1.500	3.000	6.661	1.500	2.756	XCMT10
52502053	●	P2D1531FS150A10	1.531	3.063	6.723	1.500	2.756	XCMT10
52502016	●	P2D1563FS150A12	1.563	3.125	7.063	1.500	2.756	XCMT12
52502054	●	P2D1594FS150A12	1.594	3.188	7.125	1.500	2.756	XCMT12
52502017	●	P2D1625FS150A12	1.625	3.250	7.187	1.500	2.756	XCMT12
52502055	●	P2D1656FS150A12	1.656	3.313	7.249	1.500	2.756	XCMT12
52502018	●	P2D1688FS150A12	1.688	3.375	7.313	1.500	2.756	XCMT12
52502056	●	P2D1719FS150A12	1.719	3.438	7.375	1.500	2.756	XCMT12
52502019	●	P2D1750FS150A12	1.750	3.500	7.437	1.500	2.756	XCMT12
52502057	●	P2D1781FS150A13	1.781	3.563	7.499	1.500	2.756	XCMT13
52502058	●	P2D1813FS150A13	1.813	3.625	7.563	1.500	2.756	XCMT13
52502059	●	P2D1844FS150A13	1.844	3.688	7.625	1.500	2.756	XCMT13
52502020	●	P2D1875FS150A13	1.875	3.750	7.687	1.500	2.756	XCMT13
52502060	●	P2D1906FS150A13	1.906	3.813	7.749	1.500	2.756	XCMT13
52502061	●	P2D1938FS150A13	1.938	3.875	7.813	1.500	2.756	XCMT13
52502062	●	P2D1969FS150A14	1.969	3.938	7.875	1.500	2.756	XCMT14
52502021	●	P2D2000FS150A14	2.000	4.000	7.937	1.500	2.756	XCMT14
52502022	●	P2D2125FS150A14	2.125	4.250	8.187	1.500	2.756	XCMT14
52502023	●	P2D2250FS150A16	2.250	4.500	8.437	1.500	2.756	XCMT16
52502024	●	P2D2375FS150A16	2.375	4.750	8.687	1.500	2.756	XCMT16
52502025	●	P2D2500FS150A16	2.500	5.000	8.937	1.500	2.756	XCMT16

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



DESIGNATION EXPLANATION

P2D-0484-FS-075-A-03



See Full Detail on Page 360

P	M	K	N	S	H
Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
○	○	○	○	○	○

Material recommendation based on inserts compatible with this tool body.

○ Good ○ Best

