



## List 52511

OSG PHOENIX® PZAG, Bore



SPEED FEED
370

INSERTS
298

ACCS.
299

STEEL




PACKED
1 PIECE



EDP Number	Designation	Diameter	Drilling Depth	Body Height	Flange Diameter	Bore Diameter	Keyway Width	Keyway Depth	Min. Drill Hole Size	Max Stepover for Plunging	Applicable Insert
		D (in)	l1 (in)	H (in)	D2 (in)	d3 (in)	a (in)	b (in)	(in)	Ar Max (in)	
52511000	● PZAG13R200A075-4	2.000	1.300	2.480	1.772	0.750	0.315	0.197	1.016	0.492	ZPNT13
52511001	● PZAG13R238A075-4	2.375	1.544	2.480	1.772	0.750	0.315	0.197	1.391	0.492	ZPNT13
52511002	● PZAG13R250A075-4	2.500	1.625	2.480	1.772	0.750	0.315	0.197	1.516	0.492	ZPNT13
52511003	● PZAG13R275A100-4	2.750	1.788	2.480	2.362	1.000	0.375	0.236	1.766	0.492	ZPNT13
52511004	● PZAG17R300A100-4	3.000	1.950	2.480	2.362	1.000	0.375	0.236	1.740	0.630	ZPNT17
52511005	● PZAG17R313A100-4	3.125	2.031	2.480	2.362	1.000	0.375	0.236	1.866	0.630	ZPNT17

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



### DESIGNATION EXPLANATION

**PZAG-13-R-200-A-075-4**



See Full Detail on Page 360

P	M	K	N	S	H
Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
○	○	○	○	○	○

Material recommendation based on inserts compatible with this tool body.

○ Good ○ Best

