




List 526

OSG COBALT HSS LS-EBD, Reduced Neck

SPEED FEED 1504	HSS-Co	BR	2 FLUTE	30°		WELDON FLAT	REG	PACKED 1 PIECE
---------------------------	---------------	-----------	----------------	------------	--	--------------------	------------	--------------------------

Cutting Diameter Tolerance	
1/8" ≤ D ≤ 1"	+0.0011 / -0"



EDP Number		Diameter		Length of Cut		Overall Length		Shank Diameter	
		D (Fractional Size)	Lc (Inch)	L1 (Inch)	L (Inch)	d (Inch)			
5260100	●	1/8	0.375	0.813	2.375	0.375			
5260200	●	3/16	0.500	1.125	2.688	0.375			
5260300	●	1/4	0.625	1.500	3.063	0.375			
5260400	●	5/16	0.750	1.750	3.313	0.375			
5260500	●	3/8	0.750	1.750	3.313	0.375			
5269600	●	7/16	1.000	1.875	3.688	0.500			
5261100	●	1/2	1.000	2.250	4.000	0.500			
5262100	●	5/8	1.375	2.750	4.625	0.625			
5263100	●	3/4	1.625	3.375	5.375	0.750			
5265100	●	1	2.500	5.000	7.250	1.000			

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: Other coatings available upon request.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H							
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel							
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium											
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC				
1010	1018	1035	1045	1065	4140	4340	300	400	17-4 PH	○	○	○	○	○	○	○	○	○	○	○

○ Good ⊙ Best

