


List 546

OSG COBALT HSS CC-EML

SPEED FEED 1410-1411	HSS-Co	BR	TiCN	30°			WELDON FLAT	REG	LONG	PACKED 1 PIECE
--------------------------------	---------------	-----------	-------------	------------	--	--	--------------------	------------	-------------	--------------------------

Cutting Diameter Tolerance	
1/4" ≤ D ≤ 2"	+0.0011 / -0"



EDP Number	Diameter	Length of Cut	Overall Length	Shank Diameter	Number of Flutes	Surface Treatment
5460300	1/4	1.250	3.063	0.375	4	BRIGHT
5460308	1/4	1.250	3.063	0.375	4	TiCN
5460400	5/16	1.375	3.125	0.375	4	BRIGHT
5460408	5/16	1.375	3.125	0.375	4	TiCN
5460500	3/8	1.500	3.250	0.375	4	BRIGHT
5460508	3/8	1.500	3.250	0.375	4	TiCN
5461100	1/2	2.000	4.000	0.500	4	BRIGHT
5461500	1/2	2.000	4.000	0.500	6	BRIGHT
5461108	1/2	2.000	4.000	0.500	4	TiCN
5462100	5/8	2.500	4.625	0.625	4	BRIGHT
5462500	5/8	2.500	4.625	0.625	6	BRIGHT
5462108	5/8	2.500	4.625	0.625	4	TiCN
5463100	3/4	3.000	5.250	0.750	4	BRIGHT
5463500	3/4	3.000	5.250	0.750	6	BRIGHT
5463108	3/4	3.000	5.250	0.750	4	TiCN
5464100	7/8	3.500	5.750	0.875	4	BRIGHT
5464500	7/8	3.500	5.750	0.875	6	BRIGHT
5464108	7/8	3.500	5.750	0.875	4	TiCN
5465100	1	4.000	6.500	1.000	4	BRIGHT
5465500	1	4.000	6.500	1.000	6	BRIGHT
5465108	1	4.000	6.500	1.000	4	TiCN
5466100	1-1/4	4.000	6.500	1.250	4	BRIGHT
5466500	1-1/4	4.000	6.500	1.250	6	BRIGHT
5466600	1-1/2	4.000	6.500	1.250	6	BRIGHT
5466400	2	4.000	6.500	1.250	6	BRIGHT
5468400	2	4.000	7.750	2.000	6	BRIGHT
5469400	2	6.000	9.750	2.000	6	BRIGHT

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: Other coatings available upon request.

STE

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel			
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340				7075								
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

