

List 5700

A BRAND ADF-2D, Flat Drill



SPEED FEED
318-319

CARBIDE

IchAda

EgiAs


2 FLUTE

STUB

20°

SHANK
h6

PACKED
1 PIECE



Cutting Diameter Tolerance		
Size (mm)	mm	inch
D < 2	+0 / -0.009	+0 / -0.0004
2 < D ≤ 3	+0 / -0.014	+0 / -0.0006
3 < D ≤ 6	+0 / -0.018	+0 / -0.0007
6 < D ≤ 10	+0 / -0.022	+0 / -0.0009
10 < D ≤ 18	+0 / -0.027	+0 / -0.0011
18 < D ≤ 20	+0 / -0.033	+0 / -0.0013

EDP Number		Diameter (D)					Flute Length FL (mm)	Neck Length L1 (mm)	Overall Length L (mm)	Shank Diameter		Type
		Fractional Size	Wire Gage	Letter Size	mm	Inch				d (in)	d (mm)	
3330020	●	-	-	-	0.200	0.00787	0.60	0.70	40.00	-	3.00	1
3330025	●	-	-	-	0.250	0.00984	0.80	0.90	40.00	-	3.00	1
3330030	●	-	-	-	0.300	0.01181	0.90	1.00	40.00	-	3.00	1
3330035	●	-	-	-	0.350	0.01378	1.10	1.20	40.00	-	3.00	1
570001511	●	1/64	-	-	0.397	0.01563	1.20	1.30	40.00	-	3.00	1
3330040	●	-	-	-	0.400	0.01575	1.20	1.30	40.00	-	3.00	1
3330045	●	-	-	-	0.450	0.01772	1.40	1.50	40.00	-	3.00	1
3330050	●	-	-	-	0.500	0.01969	1.70	1.90	40.00	-	3.00	1
3330055	●	-	-	-	0.550	0.02165	1.90	2.10	40.00	-	3.00	1
3330060	●	-	-	-	0.600	0.02362	2.00	2.20	40.00	-	3.00	1
3330065	●	-	-	-	0.650	0.02559	2.20	2.40	40.00	-	3.00	1
3330070	●	-	-	-	0.700	0.02756	2.40	2.60	40.00	-	3.00	1
3330071	●	-	-	-	0.710	0.02795	2.40	2.60	40.00	-	3.00	1
3330072	●	-	-	-	0.720	0.02835	2.40	2.60	40.00	-	3.00	1
3330074	●	-	-	-	0.740	0.02913	2.50	2.70	40.00	-	3.00	1
3330075	●	-	-	-	0.750	0.02953	2.60	2.80	40.00	-	3.00	1
570003111	●	1/32	-	-	0.794	0.03125	2.70	2.90	40.00	-	3.00	1
3330080	●	-	-	-	0.800	0.03150	2.70	2.90	40.00	-	3.00	1
3330081	●	-	-	-	0.810	0.03189	2.80	3.00	40.00	-	3.00	1
3330085	●	-	-	-	0.850	0.03346	2.90	3.10	40.00	-	3.00	1
3330089	●	-	-	-	0.890	0.03504	3.00	3.20	40.00	-	3.00	1
3330090	●	-	-	-	0.900	0.03543	3.10	3.30	40.00	-	3.00	1
3330091	●	-	-	-	0.910	0.03583	3.10	3.30	40.00	-	3.00	1
3330092	●	-	-	-	0.920	0.03622	3.10	3.30	40.00	-	3.00	1
3330095	●	-	-	-	0.950	0.03740	3.20	3.40	40.00	-	3.00	1
3330100	●	-	-	-	1.000	0.03937	4.00	4.30	45.00	-	3.00	1
3330109	●	-	-	-	1.090	0.04291	4.40	4.70	45.00	-	3.00	1
3330110	●	-	-	-	1.100	0.04331	4.40	4.70	45.00	-	3.00	1
3330111	●	-	-	-	1.110	0.04370	4.40	4.70	45.00	-	3.00	1
3330112	●	-	-	-	1.120	0.04409	4.50	4.80	45.00	-	3.00	1
570004611	●	3/64	-	-	1.191	0.04688	4.80	5.10	45.00	-	3.00	1
3330120	●	-	-	-	1.200	0.04724	4.80	5.10	45.00	-	3.00	1
3330125	●	-	-	-	1.250	0.04921	5.00	5.30	45.00	-	3.00	1
3330126	●	-	-	-	1.260	0.04961	5.00	5.30	45.00	-	3.00	1
3330127	●	-	-	-	1.270	0.05000	5.10	5.40	45.00	-	3.00	1
3330128	●	-	-	-	1.280	0.05039	5.10	5.40	45.00	-	3.00	1
3330129	●	-	-	-	1.290	0.05079	5.20	5.50	45.00	-	3.00	1
3330130	●	-	-	-	1.300	0.05118	5.20	5.50	45.00	-	3.00	1
3330135	●	-	-	-	1.350	0.05315	5.40	5.70	45.00	-	3.00	1
3330140	●	-	-	-	1.400	0.05512	5.60	5.90	45.00	-	3.00	1
3330144	●	-	-	-	1.440	0.05669	5.80	6.10	45.00	-	3.00	1
3330145	●	-	-	-	1.450	0.05709	5.80	6.10	45.00	-	3.00	1
3330146	●	-	-	-	1.460	0.05748	5.80	6.10	45.00	-	3.00	1

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Sizes smaller than 2mm available with IchAda coating. Sizes 2mm and larger available with EgiAs coating.



CONTINUED

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium				
Low	Medium	High						6061	7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	○	○	○	○	○	○		○	○	○	○	
1018	1045				○	○	○	○	○	○		○	○	○	○	

○ Good ○ Best





List 5700

A BRAND ADF-2D, Flat Drill



SPEED FEED
318-319

CARBIDE

IchAda

EgiAs


2 FLUTE

STUB

20°

SHANK
h6

PACKED
1 PIECE



Cutting Diameter Tolerance		
Size (mm)	mm	inch
D < 2	+0 / -0.009	+0 / -0.0004
2 < D ≤ 3	+0 / -0.014	+0 / -0.0006
3 < D ≤ 6	+0 / -0.018	+0 / -0.0007
6 < D ≤ 10	+0 / -0.022	+0 / -0.0009
10 < D ≤ 18	+0 / -0.027	+0 / -0.0011
18 < D ≤ 20	+0 / -0.033	+0 / -0.0013

EDP Number	Fractional Size	Diameter (D)				Flute Length FL (mm)	Neck Length L1 (mm)	Overall Length L (mm)	Shank Diameter		Type	
		Wire Gage	Letter Size	mm	Inch				d (in)	d (mm)		
3330147		-	-	-	1.470	0.05787	5.90	6.20	45.00	-	3.00	1
3330148		-	-	-	1.480	0.05827	5.90	6.20	45.00	-	3.00	1
3330150		-	-	-	1.500	0.05906	6.00	6.30	45.00	-	3.00	1
3330153		-	-	-	1.530	0.06024	6.10	6.40	45.00	-	3.00	1
3330154		-	-	-	1.540	0.06063	6.20	6.50	45.00	-	3.00	1
3330155		-	-	-	1.550	0.06102	6.20	6.50	45.00	-	3.00	1
3330156		-	-	-	1.560	0.06142	6.20	6.50	45.00	-	3.00	1
3330157		-	-	-	1.570	0.06181	6.30	6.60	45.00	-	3.00	1
3330158		-	-	-	1.580	0.06220	6.30	6.60	45.00	-	3.00	1
570006211	1/16	-	-	-	1.588	0.06250	6.40	6.70	45.00	-	3.00	1
3330160		-	-	-	1.600	0.06299	6.40	6.70	45.00	-	3.00	1
3330170		-	-	-	1.700	0.06693	6.80	7.10	45.00	-	3.00	1
3330175		-	-	-	1.750	0.06890	7.00	7.30	45.00	-	3.00	1
3330180		-	-	-	1.800	0.07087	7.20	7.50	45.00	-	3.00	1
3330182		-	-	-	1.820	0.07165	7.30	7.60	45.00	-	3.00	1
3330183		-	-	-	1.830	0.07205	7.30	7.60	45.00	-	3.00	1
3330184		-	-	-	1.840	0.07244	7.40	7.70	45.00	-	3.00	1
3330185		-	-	-	1.850	0.07283	7.40	7.70	45.00	-	3.00	1
3330186		-	-	-	1.860	0.07323	7.40	7.70	45.00	-	3.00	1
3330190		-	-	-	1.900	0.07480	7.60	7.90	45.00	-	3.00	1
3330195		-	-	-	1.950	0.07677	7.80	8.10	45.00	-	3.00	1
570007811	5/64	-	-	-	1.984	0.07813	7.90	8.20	45.00	-	3.00	1
3330200		-	-	-	2.000	0.07874	10.00	10.30	50.00	-	4.00	1
3330210		-	-	-	2.100	0.08268	10.00	10.50	50.00	-	4.00	1
3330220		-	-	-	2.200	0.08661	11.00	10.60	50.00	-	4.00	1
3330230		-	-	-	2.300	0.09055	11.00	10.80	50.00	-	4.00	1
570009311	3/32	-	-	-	2.381	0.09375	11.00	11.00	50.00	-	4.00	1
3330240		-	-	-	2.400	0.09449	12.00	11.00	50.00	-	4.00	1
3330250		-	-	-	2.500	0.09843	12.00	11.20	50.00	-	4.00	1
3330260		-	-	-	2.600	0.10236	13.00	11.40	50.00	-	4.00	1
3330270		-	-	-	2.700	0.10630	13.00	11.60	50.00	-	4.00	1
3330280		-	-	-	2.800	0.11024	14.00	11.80	50.00	-	4.00	1
3330290		-	-	-	2.900	0.11417	14.00	11.90	50.00	-	4.00	1
3330300		-	-	-	3.000	0.11811	15.00	11.40	55.00	-	6.00	1
3330310		-	-	-	3.100	0.12205	15.00	11.60	55.00	-	6.00	1
570012511	1/8	-	-	-	3.175	0.12500	15.00	17.00	55.00	0.125	-	2
3330320		-	-	-	3.200	0.12598	15.00	11.80	55.00	-	6.00	1
3330330		-	-	-	3.300	0.12992	15.00	12.00	55.00	-	6.00	1
3330340		-	-	-	3.400	0.13386	16.00	12.10	55.00	-	6.00	1
3330350		-	-	-	3.500	0.13780	16.00	12.30	55.00	-	6.00	1
3330360		-	-	-	3.600	0.14173	16.00	12.50	55.00	-	6.00	1
3330370		-	-	-	3.700	0.14567	16.00	12.70	55.00	-	6.00	1
3330380		-	-	-	3.800	0.14961	19.00	17.90	60.00	-	6.00	1
3330390		-	-	-	3.900	0.15354	19.00	18.10	60.00	-	6.00	1
570015611	5/32	-	-	-	3.969	0.15625	19.00	20.50	60.00	0.188	-	1
3330400		-	-	-	4.000	0.15748	19.00	18.30	60.00	-	6.00	1
3330410		-	-	-	4.100	0.16142	19.00	18.50	60.00	-	6.00	1
3330420		-	-	-	4.200	0.16535	21.00	18.60	60.00	-	6.00	1
3330430		-	-	-	4.300	0.16929	21.00	18.80	60.00	-	6.00	1
3330440		-	-	-	4.400	0.17323	21.00	19.00	60.00	-	6.00	1
3330450		-	-	-	4.500	0.17717	21.00	19.20	60.00	-	6.00	1
3330460		-	-	-	4.600	0.18110	21.00	19.40	60.00	-	6.00	1

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Sizes smaller than 2mm available with IchAda coating. Sizes 2mm and larger available with EgiAs coating.



List 5700 (Continued)

A BRAND ADF-2D, Flat Drill



SPEED FEED 318-319	CARBIDE	IchAda	EgiAs	2 FLUTE	STUB	20°	SHANK h6	PACKED 1 PIECE
------------------------------	----------------	---------------	--------------	----------------	-------------	------------	--------------------	--------------------------

EDP Number		Diameter (D)					Flute Length	Neck Length	Overall Length	Shank Diameter		Type
		Fractional Size	Wire Gage	Letter Size	mm	Inch	FL (mm)	L1 (mm)	L (mm)	d (in)	d (mm)	
3330470	●	-	-	-	4.700	0.18504	21.00	19.60	60.00	-	6.00	1
570018711	●	3/16	-	-	4.763	0.18750	24.00	27.00	65.00	0.188	-	2
3330480	●	-	-	-	4.800	0.18898	24.00	24.80	65.00	-	6.00	1
3330490	●	-	-	-	4.900	0.19291	24.00	24.90	65.00	-	6.00	1
3330500	●	-	-	-	5.000	0.19685	24.00	25.10	65.00	-	6.00	1
3330510	●	-	-	-	5.100	0.20079	24.00	25.30	65.00	-	6.00	1
3330520	●	-	-	-	5.200	0.20472	24.00	25.50	65.00	-	6.00	1
3330530	●	-	-	-	5.300	0.20866	24.00	25.70	65.00	-	6.00	1
3330540	●	-	-	-	5.400	0.21260	27.00	25.90	65.00	-	6.00	1
3330550	●	-	-	-	5.500	0.21654	27.00	26.10	65.00	-	6.00	1
570021811	●	7/32	-	-	5.556	0.21875	27.00	25.50	65.00	0.250	-	1
3330560	●	-	-	-	5.600	0.22047	27.00	26.30	65.00	-	6.00	1
3330570	●	-	-	-	5.700	0.22441	27.00	26.40	65.00	-	6.00	1
3330580	●	-	-	-	5.800	0.22835	27.00	26.60	65.00	-	6.00	1
3330590	●	-	-	-	5.900	0.23228	27.00	26.80	65.00	-	6.00	1
3330600	●	-	-	-	6.000	0.23622	27.00	27.00	65.00	-	6.00	2
3330610	●	-	-	-	6.100	0.24016	30.00	32.00	70.00	-	6.00	2
3330620	●	-	-	-	6.200	0.24409	30.00	32.00	70.00	-	6.00	2
3330630	●	-	-	-	6.300	0.24803	30.00	32.00	70.00	-	6.00	2
570025011	●	1/4	-	E	6.350	0.25000	30.00	32.00	70.00	0.250	-	2
3330640	●	-	-	-	6.400	0.25197	30.00	32.00	70.00	-	6.00	2
3330650	●	-	-	-	6.500	0.25591	30.00	32.00	70.00	-	6.00	2
3330660	●	-	-	-	6.600	0.25984	30.00	32.00	70.00	-	6.00	2
3330670	●	-	-	-	6.700	0.26378	30.00	32.00	70.00	-	6.00	2
3330680	●	-	-	-	6.800	0.26772	30.00	32.00	70.00	-	6.00	2
3330690	●	-	-	-	6.900	0.27165	30.00	32.00	70.00	-	6.00	2
3330700	●	-	-	-	7.000	0.27559	30.00	32.00	70.00	-	6.00	2
3330710	●	-	-	-	7.100	0.27953	34.00	36.00	75.00	-	6.00	2
570028111	●	9/32	-	-	7.144	0.28125	34.00	34.50	75.00	0.313	-	1
3330720	●	-	-	-	7.200	0.28346	34.00	36.00	75.00	-	6.00	2
3330730	●	-	-	-	7.300	0.28740	34.00	36.00	75.00	-	6.00	2
3330740	●	-	-	-	7.400	0.29134	34.00	36.00	75.00	-	6.00	2
3330750	●	-	-	-	7.500	0.29528	34.00	36.00	75.00	-	6.00	2
3330760	●	-	-	-	7.600	0.29921	34.00	36.00	75.00	-	6.00	2
3330770	●	-	-	-	7.700	0.30315	34.00	36.00	75.00	-	6.00	2
3330780	●	-	-	-	7.800	0.30709	34.00	36.00	75.00	-	6.00	2
3330790	●	-	-	-	7.900	0.31102	34.00	36.00	75.00	-	6.00	2
570031211	●	5/16	-	-	7.938	0.31250	34.00	36.00	75.00	0.313	-	2
3330800	●	-	-	-	8.000	0.31496	34.00	36.00	75.00	-	8.00	2
3330810	●	-	-	-	8.100	0.31890	38.00	40.00	80.00	-	8.00	2
3330820	●	-	-	-	8.200	0.32283	38.00	40.00	80.00	-	8.00	2
3330830	●	-	-	-	8.300	0.32677	38.00	40.00	80.00	-	8.00	2
570032811	●	21/64	-	-	8.334	0.32813	38.00	37.80	80.00	0.375	-	1
3330840	●	-	-	-	8.400	0.33071	38.00	40.00	80.00	-	8.00	2
3330850	●	-	-	-	8.500	0.33465	38.00	40.00	80.00	-	8.00	2
3330860	●	-	-	-	8.600	0.33858	38.00	40.00	80.00	-	8.00	2
3330870	●	-	-	-	8.700	0.34252	38.00	40.00	80.00	-	8.00	2
3330880	●	-	-	-	8.800	0.34646	38.00	40.00	80.00	-	8.00	2

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Sizes smaller than 2mm available with IchAda coating. Sizes 2mm and larger available with EgiAs coating.



CONTINUED ➔

P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best






List 5700 (Continued)

A BRAND ADF-2D, Flat Drill



SPEED FEED 318-319	CARBIDE	IchAda	EgiAs	2 FLUTE	STUB	20°	SHANK h6	PACKED 1 PIECE
------------------------------	----------------	---------------	--------------	----------------	-------------	------------	--------------------	--------------------------



Cutting Diameter Tolerance		
Size (mm)	mm	inch
D < 2	+0 / -0.009	+0 / -0.0004
2 < D ≤ 3	+0 / -0.014	+0 / -0.0006
3 < D ≤ 6	+0 / -0.018	+0 / -0.0007
6 < D ≤ 10	+0 / -0.022	+0 / -0.0009
10 < D ≤ 18	+0 / -0.027	+0 / -0.0011
18 < D ≤ 20	+0 / -0.033	+0 / -0.0013

EDP Number	●	Diameter (D)					Flute Length FL (mm)	Neck Length L1 (mm)	Overall Length L (mm)	Shank Diameter		Type
		Fractional Size	Wire Gage	Letter Size	mm	Inch				d (in)	d (mm)	
3330890	●	-	-	-	8.900	0.35039	38.00	40.00	80.00	-	8.00	2
3330900	●	-	-	-	9.000	0.35433	38.00	40.00	80.00	-	8.00	2
3330910	●	-	-	-	9.100	0.35827	42.00	44.00	85.00	-	8.00	2
570035911	●	23/64	-	-	9.128	0.35938	42.00	43.30	85.00	0.375	-	1
3330920	●	-	-	-	9.200	0.36220	42.00	44.00	85.00	-	8.00	2
3330930	●	-	-	-	9.300	0.36614	42.00	44.00	85.00	-	8.00	2
3330940	●	-	-	-	9.400	0.37008	42.00	44.00	85.00	-	8.00	2
3330950	●	-	-	-	9.500	0.37402	42.00	44.00	85.00	-	8.00	2
570037511	●	3/8	-	-	9.525	0.37500	42.00	44.00	85.00	0.375	-	2
3330960	●	-	-	-	9.600	0.37795	42.00	44.00	85.00	-	8.00	2
3330970	●	-	-	-	9.700	0.38189	42.00	44.00	85.00	-	8.00	2
3330980	●	-	-	-	9.800	0.38583	42.00	44.00	85.00	-	8.00	2
3330990	●	-	-	-	9.900	0.38976	42.00	44.00	85.00	-	8.00	2
3331000	●	-	-	-	10.000	0.39370	42.00	44.00	85.00	-	10.00	2
3331010	●	-	-	-	10.100	0.39764	46.00	48.00	90.00	-	10.00	2
3331020	●	-	-	-	10.200	0.40157	46.00	48.00	90.00	-	10.00	2
3331030	●	-	-	-	10.300	0.40551	46.00	48.00	90.00	-	10.00	2
570040611	●	13/32	-	-	10.319	0.40625	46.00	46.50	90.00	0.438	-	1
3331040	●	-	-	-	10.400	0.40945	46.00	48.00	90.00	-	10.00	2
3331050	●	-	-	-	10.500	0.41339	46.00	48.00	90.00	-	10.00	2
3331060	●	-	-	-	10.600	0.41732	46.00	48.00	90.00	-	10.00	2
3331070	●	-	-	-	10.700	0.42126	46.00	48.00	90.00	-	10.00	2
3331080	●	-	-	-	10.800	0.42520	46.00	48.00	90.00	-	10.00	2
3331090	●	-	-	-	10.900	0.42913	46.00	48.00	90.00	-	10.00	2
3331100	●	-	-	-	11.000	0.43307	46.00	48.00	90.00	-	10.00	2
3331110	●	-	-	-	11.100	0.43701	50.00	52.00	95.00	-	10.00	2
570043711	●	7/16	-	-	11.113	0.43750	50.00	52.00	95.00	0.438	-	2
3331120	●	-	-	-	11.200	0.44094	50.00	52.00	95.00	-	10.00	2
3331130	●	-	-	-	11.300	0.44488	50.00	52.00	95.00	-	10.00	2
3331140	●	-	-	-	11.400	0.44882	50.00	52.00	95.00	-	10.00	2
3331150	●	-	-	-	11.500	0.45276	50.00	52.00	95.00	-	10.00	2
570045311	●	29/64	-	-	11.509	0.45313	50.00	49.80	95.00	0.500	-	1
3331160	●	-	-	-	11.600	0.45669	50.00	52.00	95.00	-	10.00	2
3331170	●	-	-	-	11.700	0.46063	50.00	52.00	95.00	-	10.00	2
3331180	●	-	-	-	11.800	0.46457	50.00	52.00	95.00	-	10.00	2
3331190	●	-	-	-	11.900	0.46850	50.00	52.00	95.00	-	10.00	2
570046811	●	15/32	-	-	11.906	0.46875	50.00	50.50	95.00	0.500	-	1
3331200	●	-	-	-	12.000	0.47244	50.00	52.00	95.00	-	12.00	2
3331210	●	-	-	-	12.100	0.47638	56.00	58.00	100.00	-	12.00	2
3331220	●	-	-	-	12.200	0.48031	56.00	58.00	100.00	-	12.00	2
3331230	●	-	-	-	12.300	0.48425	56.00	58.00	100.00	-	12.00	2
3331240	●	-	-	-	12.400	0.48819	56.00	58.00	100.00	-	12.00	2
3331250	●	-	-	-	12.500	0.49213	56.00	58.00	100.00	-	12.00	2
3331260	●	-	-	-	12.600	0.49606	56.00	58.00	100.00	-	12.00	2
3331270	●	1/2	-	-	12.700	0.50000	56.00	58.00	100.00	-	12.00	2
3331280	●	-	-	-	12.800	0.50394	56.00	58.00	100.00	-	12.00	2
3331290	●	-	-	-	12.900	0.50787	56.00	58.00	100.00	-	12.00	2
3331300	●	-	-	-	13.000	0.51181	56.00	58.00	100.00	-	12.00	2
3331310	●	-	-	-	13.100	0.51575	60.00	62.00	105.00	-	12.00	2
3331320	●	-	-	-	13.200	0.51969	60.00	62.00	105.00	-	12.00	2
3331330	●	-	-	-	13.300	0.52362	60.00	62.00	105.00	-	12.00	2
3331340	●	-	-	-	13.400	0.52756	60.00	62.00	105.00	-	12.00	2

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: Sizes smaller than 2mm available with IchAda coating. Sizes 2mm and larger available with EgiAs coating.



List 5700 (Continued)

A BRAND ADF-2D, Flat Drill



SPEED FEED
318-319

CARBIDE

IchAda

EgiAs

2 FLUTE

STUB

20°

SHANK
h6

PACKED
1 PIECE

EDP Number		Diameter (D)					Flute Length	Neck Length	Overall Length	Shank Diameter		Type
		Fractional Size	Wire Gage	Letter Size	mm	Inch				d (in)	d (mm)	
3331350	●	-	-	-	13.500	0.53150	60.00	62.00	105.00	-	12.00	2
3331360	●	-	-	-	13.600	0.53543	60.00	62.00	105.00	-	12.00	2
3331370	●	-	-	-	13.700	0.53937	60.00	62.00	105.00	-	12.00	2
3331380	●	-	-	-	13.800	0.54331	60.00	62.00	105.00	-	12.00	2
3331390	●	-	-	-	13.900	0.54724	60.00	62.00	105.00	-	12.00	2
3331400	●	-	-	-	14.000	0.55118	60.00	62.00	105.00	-	12.00	2
3331410	●	-	-	-	14.100	0.55512	64.00	66.00	110.00	-	12.00	2
3331420	●	-	-	-	14.200	0.55906	64.00	66.00	110.00	-	12.00	2
570056211	●	9/16	-	-	14.288	0.56250	64.00	63.00	110.00	0.625	-	1
3331430	●	-	-	-	14.300	0.56299	64.00	66.00	110.00	-	12.00	2
3331440	●	-	-	-	14.400	0.56693	64.00	66.00	110.00	-	12.00	2
3331450	●	-	-	-	14.500	0.57087	64.00	66.00	110.00	-	12.00	2
3331460	●	-	-	-	14.600	0.57480	64.00	66.00	110.00	-	12.00	2
3331470	●	-	-	-	14.700	0.57874	64.00	66.00	110.00	-	12.00	2
3331480	●	-	-	-	14.800	0.58268	64.00	66.00	110.00	-	12.00	2
3331490	●	-	-	-	14.900	0.58661	64.00	66.00	110.00	-	12.00	2
3331500	●	-	-	-	15.000	0.59055	64.00	66.00	110.00	-	12.00	2
3331510	●	-	-	-	15.100	0.59449	68.00	70.00	115.00	-	12.00	2
3331520	●	-	-	-	15.200	0.59843	68.00	70.00	115.00	-	12.00	2
3331530	●	-	-	-	15.300	0.60236	68.00	70.00	115.00	-	12.00	2
3331540	●	-	-	-	15.400	0.60630	68.00	70.00	115.00	-	12.00	2
3331550	●	-	-	-	15.500	0.61024	68.00	70.00	115.00	-	12.00	2
3331560	●	-	-	-	15.600	0.61417	68.00	70.00	115.00	-	12.00	2
3331570	●	-	-	-	15.700	0.61811	68.00	70.00	115.00	-	12.00	2
3331580	●	-	-	-	15.800	0.62205	68.00	70.00	115.00	-	12.00	2
570062511	●	5/8	-	-	15.875	0.62500	68.00	70.00	115.00	0.625	-	2
3331590	●	-	-	-	15.900	0.62598	68.00	70.00	115.00	-	12.00	2
3331600	●	-	-	-	16.000	0.62992	68.00	70.00	115.00	-	16.00	2
3331650	●	-	-	-	16.500	0.64961	74.00	76.00	125.00	-	16.00	2
3331700	●	-	-	-	17.000	0.66929	74.00	76.00	125.00	-	16.00	2
570068711	●	11/16	-	-	17.463	0.68750	78.00	77.10	130.00	0.750	-	1
3331750	●	-	-	-	17.500	0.68898	78.00	80.00	130.00	-	16.00	2
3331800	●	-	-	-	18.000	0.70866	78.00	80.00	130.00	-	16.00	2
3331850	●	-	-	-	18.500	0.72835	84.00	86.00	135.00	-	16.00	2
3331900	●	-	-	-	19.000	0.74803	84.00	86.00	135.00	-	16.00	2
570075011	●	3/4	-	-	19.050	0.75000	88.00	90.00	140.00	0.750	-	2
3331950	●	-	-	-	19.500	0.76772	88.00	90.00	140.00	-	16.00	2
3332000	●	-	-	-	20.000	0.78740	88.00	90.00	140.00	-	20.00	2

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Sizes smaller than 2mm available with IchAda coating. Sizes 2mm and larger available with EgiAs coating.



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH	6061 7075	Casting	Inconel			6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC
1010	1035	1065	4140	4340	○	○	○	○	○	○			○	○		
1018	1045							○								

○ Good ○ Best

