



List 5955Ni

EXOPRO WHO-NI-5D

SPEED FEED
323

CARBIDE


DUREY



2 FLUTE

JOBBER

12-20°

SHANK
h6PACKED
1 PIECE

Cutting Diameter Tolerance (h8)		
Size (mm)	mm	inch
D = 3	+0 / -0.014	+0 / -0.0006
3 < D ≤ 6	+0 / -0.018	+0 / -0.0007
6 < D ≤ 10	+0 / -0.022	+0 / -0.0009
10 < D ≤ 12.7	+0 / -0.027	+0 / -0.0011

EDP Number		Diameter (D)					Flute Length FL (mm)	Overall Length L (mm)	Shank Diameter d (mm)
		Fractional Size	Wire Gage	Letter Size	mm	Inch			
595511811	●	-	-	-	3.000	0.11811	29.00	78.00	6.00
595512511	●	1/8	-	-	3.175	0.12500	29.00	78.00	6.00
3316330	●	-	-	-	3.300	0.12992	32.00	78.00	6.00
3316340	●	-	-	-	3.400	0.13386	32.00	78.00	6.00
3316349	●	-	-	-	3.490	0.13740	32.00	78.00	6.00
3316350	●	-	-	-	3.500	0.13780	32.00	78.00	6.00
595513911	●	-	-	-	3.510	0.13819	34.00	78.00	6.00
3316360	●	-	-	-	3.600	0.14173	34.00	78.00	6.00
3316370	●	-	-	-	3.700	0.14567	34.00	78.00	6.00
3316380	●	-	-	-	3.800	0.14961	36.00	78.00	6.00
3316390	●	-	-	-	3.900	0.15354	36.00	78.00	6.00
595515611	●	5/32	-	-	3.969	0.15625	36.00	78.00	6.00
3316400	●	-	-	-	4.000	0.15748	36.00	78.00	6.00
3316410	●	-	-	-	4.100	0.16142	38.00	88.00	6.00
3316415	●	-	-	-	4.150	0.16339	38.00	88.00	6.00
3316420	●	-	-	-	4.200	0.16535	38.00	88.00	6.00
3316430	●	-	-	-	4.300	0.16929	41.00	88.00	6.00
595517111	●	11/64	-	-	4.366	0.17188	41.00	88.00	6.00
3316440	●	-	-	-	4.400	0.17323	41.00	88.00	6.00
3316450	●	-	-	-	4.500	0.17717	41.00	88.00	6.00
3316460	●	-	-	-	4.600	0.18110	43.00	88.00	6.00
3316470	●	-	-	-	4.700	0.18504	43.00	88.00	6.00
595518711	●	3/16	-	-	4.763	0.18750	45.00	88.00	6.00
3316480	●	-	-	-	4.800	0.18898	45.00	88.00	6.00
3316490	●	-	-	-	4.900	0.19291	45.00	88.00	6.00
3316500	●	-	-	-	5.000	0.19685	45.00	88.00	6.00
3316510	●	-	-	-	5.100	0.20079	42.00	92.00	6.00
595520311	●	13/64	-	-	5.159	0.20313	42.00	92.00	6.00
3316520	●	-	-	-	5.200	0.20472	42.00	92.00	6.00
595520611	●	-	-	-	5.220	0.20550	44.00	92.00	6.00
3316530	●	-	-	-	5.300	0.20866	44.00	92.00	6.00
3316540	●	-	-	-	5.400	0.21260	44.00	92.00	6.00
3316550	●	-	-	-	5.500	0.21654	44.00	92.00	6.00
595521611	●	-	-	-	5.530	0.21772	46.00	92.00	6.00
595521811	●	7/32	-	-	5.556	0.21875	46.00	92.00	6.00
3316556	●	-	-	-	5.560	0.21890	46.00	92.00	6.00
3316560	●	-	-	-	5.600	0.22047	46.00	92.00	6.00
3316570	●	-	-	-	5.700	0.22441	46.00	92.00	6.00
3316580	●	-	-	-	5.800	0.22835	48.00	92.00	6.00
3316590	●	-	-	-	5.900	0.23228	48.00	92.00	6.00
595523411	●	15/64	-	-	5.953	0.23438	48.00	92.00	6.00
3316600	●	-	-	-	6.000	0.23622	48.00	92.00	6.00
595525011	●	1/4	-	-	6.350	0.25000	52.00	102.00	8.00
3316650	●	-	-	-	6.500	0.25591	52.00	102.00	8.00
595526211	●	-	-	-	6.650	0.26181	54.00	102.00	8.00
595526511	●	17/64	-	-	6.747	0.26563	55.00	102.00	8.00
3316680	●	-	-	-	6.800	0.26772	56.00	102.00	8.00
595527411	●	-	-	-	6.960	0.27402	56.00	102.00	8.00
3316700	●	-	-	-	7.000	0.27559	56.00	102.00	8.00
595528111	●	9/32	-	-	7.144	0.28125	58.00	118.00	8.00
3316750	●	-	-	-	7.500	0.29528	60.00	118.00	8.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked





List 5955Ni (Continued)

EXOPRO WHO-NI-5D



SPEED FEED 323	CARBIDE	DUOREY	2 FLUTE	JOBBER	12-20°	SHANK h6	PACKED 1 PIECE
--------------------------	----------------	---------------	----------------	---------------	---------------	--------------------	--------------------------

EDP Number		Diameter (D)					Flute Length	Overall Length	Shank Diameter
		Fractional Size	Wire Gage	Letter Size	mm	Inch	FL (mm)	L (mm)	d (mm)
595529611	●	19/64	-	-	7.541	0.29688	62.00	118.00	8.00
3316780	●	-	-	-	7.800	0.30709	64.00	118.00	8.00
595531211	●	5/16	-	-	7.938	0.31250	64.00	118.00	8.00
3316800	●	-	-	-	8.000	0.31496	64.00	118.00	8.00
595531711	●	-	-	-	8.040	0.31654	66.00	128.00	10.00
595532811	●	21/64	-	-	8.334	0.32813	68.00	128.00	10.00
3316850	●	-	-	-	8.500	0.33465	68.00	128.00	10.00
595533511	●	-	-	-	8.520	0.33543	70.00	128.00	10.00
3316858	●	-	-	-	8.580	0.33780	70.00	128.00	10.00
3316870	●	-	-	-	8.700	0.34252	70.00	128.00	10.00
595534311	●	11/32	-	-	8.731	0.34375	70.00	128.00	10.00
3316880	●	-	-	-	8.800	0.34646	72.00	128.00	10.00
3316900	●	-	-	-	9.000	0.35433	72.00	128.00	10.00
595535911	●	23/64	-	-	9.128	0.35938	74.00	136.00	10.00
595537011	●	-	-	-	9.390	0.36969	76.00	136.00	10.00
3316950	●	-	-	-	9.500	0.37402	76.00	136.00	10.00
595537511	●	3/8	-	-	9.525	0.37500	78.00	136.00	10.00
3316980	●	-	-	-	9.800	0.38583	80.00	136.00	10.00
595538911	●	-	-	-	9.900	0.38976	80.00	136.00	10.00
595539011	●	25/64	-	-	9.922	0.39063	80.00	136.00	10.00
3316997	●	-	-	-	9.970	0.39252	80.00	136.00	10.00
3317000	●	-	-	-	10.000	0.39370	80.00	136.00	10.00
3317030	●	-	-	-	10.300	0.40551	84.00	146.00	12.00
595540611	●	13/32	-	-	10.319	0.40625	84.00	146.00	12.00
3317050	●	-	-	-	10.500	0.41339	84.00	146.00	12.00
595542211	●	27/64	-	-	10.716	0.42188	88.00	146.00	12.00
3317080	●	-	-	-	10.800	0.42520	88.00	146.00	12.00
595542611	●	-	-	-	10.830	0.42638	88.00	146.00	12.00
3317100	●	-	-	-	11.000	0.43307	88.00	146.00	12.00
595543711	●	7/16	-	-	11.113	0.43750	90.00	156.00	12.00
595545211	●	-	-	-	11.470	0.45157	92.00	156.00	12.00
3317150	●	-	-	-	11.500	0.45276	92.00	156.00	12.00
595545311	●	29/64	-	-	11.509	0.45313	94.00	156.00	12.00
3317156	●	-	-	-	11.560	0.45512	94.00	156.00	12.00
3317180	●	-	-	-	11.800	0.46457	96.00	156.00	12.00
595546811	●	15/32	-	-	11.906	0.46875	96.00	156.00	12.00
3317200	●	-	-	-	12.000	0.47244	96.00	156.00	12.00
595548411	●	31/64	-	-	12.303	0.48438	100.00	167.00	14.00
595550011	●	1/2	-	-	12.700	0.50000	104.00	167.00	14.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	7075			Casting	Inconel	6Al4V (30 HRC)	~35 HRC
○	○	○	○	○				○			○	○	○	○	○	○

○ Good ○ Best

