




## List 676

EXOMINI VC-10 TIN-CPM-M-EMS

<b>SPEED FEED</b> 1410-1411	<b>VC10</b>	<b>TiN</b>	<b>4 FLUTE</b>	<b>30°</b>			<b>REG</b>	<b>PACKED</b> 1 PIECE
--------------------------------	-------------	------------	----------------	------------	--	--	------------	--------------------------



Cutting Diameter Tolerance	
1/16" ≤ D ≤ 5/32"	+0 / -0.0011"
D = 3/16"	-0.0004 / -0.0015"

EDP Number	Diameter	Length of Cut	Overall Length	Shank Diameter	Center Cutting	
						D (Fractional Size)
6767205	●	1/16	0.094	1.750	0.188	-
6767405	●	3/32	0.141	1.750	0.188	-
6767605	●	1/8	0.188	1.750	0.188	●
6767805	●	5/32	0.234	1.750	0.188	●
6768005	●	3/16	0.281	1.750	0.188	●

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel			
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	○	⊗	⊗	⊗	⊗	⊗	○	○	○		○	⊗	○		

○ Good ⊗ Best

