



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

List 7520

EXOPRO AERO-LHX, Low Helix

SPEED FEED	CARBIDE	DIA	4 FLUTE	5°	SHANK	PACKED
324					h6	1 PIECE

Cutting Diameter Tolerance
inch
+0 / -0.001



EDP Number		Diameter (D)					Flute Length FL (mm)	Taper Length l (mm)	Overall Length L (mm)	Shank Diameter d (mm)
		Fractional Size	Wire Gage	Letter Size	mm	Inch				
752009816	●	-	40	-	2.502	0.09850	15.20	7.00	50.80	2.50
752012916	●	-	30	-	3.277	0.12900	20.30	9.00	50.80	3.27
752016116	●	-	20	-	4.102	0.16150	25.40	11.20	76.20	4.10
752019216	●	-	11	-	4.864	0.19150	27.90	13.20	76.20	4.86
752022116	●	-	2	-	5.626	0.22150	33.00	15.20	88.90	5.62
752025116	●	1/4	-	-	6.375	0.25000	38.10	17.20	88.90	6.37
752031316	●	5/16	-	-	7.963	0.31250	48.20	21.40	101.60	7.96
752037616	●	3/8	-	-	9.550	0.37500	58.40	25.60	101.60	9.55
752043816	●	7/16	-	-	11.138	0.43750	66.00	29.80	101.60	11.13
752050116	●	1/2	-	-	12.725	0.50000	76.20	34.00	127.00	12.72

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: Drills are oversize over nominal.



Carbon Fiber (CFRP)	Glass Fiber (GFRP)	Aramid Fiber (AFRP)	Honeycomb					Carbon/Carbon	Carbon Fiber/Aluminum Stack	Carbon Fiber/Titanium Stack	Carbon Fiber/Al/Ti/CRES Stack
			CFRP/Nomex	GFRP/Nomex	AFRP	CFRP/Al	Al/Al				
○	○		○	○		○					

○ Good ○ Best

