




List 7808H

OSG PHOENIX® PFB ACCESSORIES

PACKED	PACKED
1 PIECE	10 PIECE

Appearance	EDP No.		Designation	Applicable Cutter		Recommended Tightening Torque
				Inch	mm	
 Clamping Screw	7808124	●	FS20652RB (Torx 6)	PFB SA Ø0.250	PFB SS Ø6-7	0.4 Nm
	7808123	●	FS25669RB (Torx 7)	-	PFB SS Ø8	1.0 Nm
	7808117	●	FS30686RB (Torx 8)	PFB SA/ASF Ø0.375	PFB SS/SF Ø10	1.2 Nm
	7808118	●	FS35610RB (Torx 10)	PFB SA/ASF Ø0.500	PFB SS/SF Ø12	2.0 Nm
	7808119	●	FS40613RB (Torx 15)	PFB SA/ASF Ø0.625	PFB SS/SF Ø16	3.0 Nm
	7808120	●	FS50615RB (Torx 20)	PFB SA/ASF Ø0.750	PFB SS/SF Ø20	5.0 Nm
	7808121	●	FS60620RB (Torx 20)	PFB SA/ASF Ø1.000	PFB SS/SF Ø25	5.0 Nm
	7808122	●	FS80624RB (Torx 30)	PFB SA Ø1.250	PFB SS/SF Ø30-32	6.0 Nm
 Wrench	7808203	●	T6-D (Torx 6)	PFB SA Ø0.250	PFB SS Ø6-7	-
	7808204	●	T7-D (Torx 7)	-	PFB SS Ø8	-
	7808205	●	T8-D (Torx 8)	PFB SA/ASF Ø0.375	PFB SS/SF Ø10	-
	7808207	●	T10-D (Torx 10)	PFB SA/ASF Ø0.500	PFB SS/SF Ø12	-
	7808208	●	T15-D (Torx 15)	PFB SA/ASF Ø0.625	PFB SS/SF Ø16	-
	7808209	●	T20-D (Torx 20)	PFB SA/ASF Ø0.750	PFB SS/SF Ø20-25	-
 T-Handle Wrench	7808212	●	T30-T (Torx 30)	PFB SA Ø1.250	PFB SS/SF Ø30-32	-

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
Note: Wrench sold separately
Packed: Clamping Screws = 1 pc.; T-Handle Wrench = 1 pc.; Wrench = 1 pc.

PXT

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

