





List 7808H

OSG PHOENIX[®] PRC ACCESSORIES

PACKED	PACKED
1 PIECE	10 PIECE

Appearance	EDP No.		Designation	Applicable Insert	Applicable Cutter		Recommended Tightening Torque
					Inch	mm	
 Clamping Screw	7808116	●	FS30573A (M3 x 7.3, Torx 10)	RPH_10	PRC SA/ASF Ø1.000-1.250, PRC BORE Ø2.000-2.500	PRC SS/SF Ø20-32	2.0 Nm
	7808112	●	FS35586 (M3.5 x 8.6, Torx 15)	RPH_12	PRC SA/ASF Ø1.250-1.500, PRC BORE Ø2.000-4.000	PRC SS/SF Ø32-50, PRC BORE Ø32-63	3.2 Nm
	7808113	●	FS45510 (M4.5 x 10.5, Torx 20)	RPH_16	PRC SA/ASF Ø1.500, PRC BORE Ø2.000-6.000	PRC SS/SF Ø40-63, PRC BORE Ø50-100	5.0 Nm
 Power Screw	7808151	●	PS1031 (M10x31)	-	-	PRC BORE Ø50	20.0 Nm
 Wrench	7808207	●	T10-D (Torx 10)	RPH_10	PRC SA/ASF Ø1.000-1.250, PRC BORE Ø2.000-2.500	PRC SS/SF Ø20-32	-
	7808208	●	T15-D (Torx 15)	RPH_12	PRC SA/ASF Ø1.250-1.500, PRC BORE Ø2.000-4.000	PRC SS/SF Ø32-50, PRC BORE Ø32-63	-
	7808209	●	T20-D (Torx 20)	RPH_16	PRC SA/ASF Ø1.500, PRC BORE Ø2.000-6.000	PRC SS/SF Ø40-63, PRC BORE Ø50-100	-

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
Note: Wrench sold separately
Packed: Clamping Screws = 10 pcs.; Power Screw = 1 pc.; Wrench = 1 pc.

PXT

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

