



## List 805

OSG Carbide Bur SM-Pointed Cone

SPEED FEED 1518	CARBIDE	BR	STUB	REG	LONG	PACKED 1 PIECE
--------------------	---------	----	------	-----	------	-------------------



EDP Number		Diameter		Length of Cut		Included Angle	Overall Length		Shank Diameter		Style
		D (Fractional Size)	D (mm)	Lc (Inch)	Lc (mm)	$\alpha$ (°)	L (Inch)	L (mm)	d (Inch)	d (mm)	
805-2362	●	-	6.00	-	12.70	22.00	-	50.00	-	6.00	SM-1M
805-2363	●	-	6.00	-	19.00	14.00	-	50.00	-	6.00	SM-2M
805-2364	●	-	6.00	-	25.00	10.00	-	50.00	-	6.00	SM-3M
805-2500	●	1/4	-	0.500	-	22.00	2.000	-	0.250	-	SM-1
805-2501	●	1/4	-	0.750	-	14.00	2.000	-	0.250	-	SM-2
805-2502	●	1/4	-	1.000	-	10.00	2.000	-	0.250	-	SM-3
805-3750	●	3/8	-	0.625	-	28.00	2.500	-	0.250	-	SM-4
805-3750-60	●	-	9.50	-	16.00	28.00	-	63.00	-	6.00	SM-4M
805-5000	●	1/2	-	0.875	-	28.00	2.750	-	0.250	-	SM-5
805-5000-60	●	-	12.70	-	22.00	28.00	-	69.00	-	6.00	SM-5M
805-6250	●	5/8	-	1.000	-	31.00	2.925	-	0.250	-	SM-6
805-6250-60	●	-	16.00	-	25.00	31.00	-	73.00	-	6.00	SM-6M

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Tool diameter  $\leq 1/4"$  / 6mm have brazed carbide shanks, all others have hardened steel shanks.