



List 882

OSG Carbide Bur SC-Cylindrical Ball End

SPEED FEED 1518	CARBIDE	BR	STUB	REG	LONG	PACKED 1 PIECE
---------------------------	----------------	-----------	-------------	------------	-------------	--------------------------



EDP Number		Diameter		Length of Cut		Overall Length		Shank Diameter		Style
		D (Fractional Size)	D (mm)	Lc (Inch)	Lc (mm)	L (Inch)	L (mm)	d (Inch)	d (mm)	
882-2362	●	-	6.00	-	19.00	-	50.00	-	6.00	SC-1MA
882-2500	●	1/4	-	0.750	-	2.000	-	0.250	-	SC-1A
882-3750	●	3/8	-	0.750	-	2.750	-	0.250	-	SC-3A
882-5000	●	1/2	-	1.000	-	2.750	-	0.250	-	SC-5A
882-5000-60	●	-	12.70	-	25.00	-	69.00	-	6.00	SC-5MA
882-6250-60	●	-	16.00	-	25.00	-	69.00	-	6.00	SC-6MA
882-6250	●	5/8	-	1.000	-	3.000	-	0.250	-	SC-6A
882-3750-60	●	-	9.50	-	19.00	-	63.00	-	6.00	SC-3MA
882-7500	●	3/4	-	1.000	-	2.750	-	0.250	-	SC-7A
882-7500-60	●	-	19.00	-	25.00	-	69.00	-	6.00	SC-7MA

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Tool diameter ≤ 1/4" / 6mm have brazed carbide shanks, all others have hardened steel shanks.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

