




PACKED
1 PIECE

List 9902

HY-PRO® Shrink Mono Holders, For Standard & Coolant-Through the Tool Operations



HSK-E25 Mono Series

| EDP Number | Designation | Body Type | Bore Diameter | Nose Diameter | Neck Length | | Neck Diameter | Body Diameter | Overall Length | Clamping Length | Max Insertion Length |
|------------|--------------------|-----------------|---------------|---------------|-------------|---------|---------------|---------------|----------------|-----------------|----------------------|
| | | | d3 (mm) | C (mm) | L1 (mm) | L2 (mm) | d1 (mm) | D3 (mm) | L (mm) | H (mm) | H1 (mm) |
| 9911101 | ● E25-SLRA3-35 | HSK-E25 Regular | 3.0 | 7.5 | 17.0 | 8.0 | 9.3 | 18.0 | 35.0 | 9.0 | 29.0 |
| 9911102 | ● E25-SLRA4-35 | HSK-E25 Regular | 4.0 | 10.0 | 17.0 | 8.0 | 11.8 | 18.0 | 35.0 | 12.0 | 29.0 |
| 9911103 | ● E25-SLRA6-35 | HSK-E25 Regular | 6.0 | 12.0 | 17.0 | 8.0 | 13.8 | 18.0 | 35.0 | 18.0 | 26.0 |
| 9911104 | ● E25-SLSA3-35 | HSK-E25 Slim | 3.0 | 6.0 | 17.0 | 8.0 | 7.8 | 18.0 | 35.0 | 9.0 | 29.0 |
| 9911105 | ● E25-SLSA3-50 | HSK-E25 Slim | 3.0 | 6.0 | 32.0 | 8.0 | 9.4 | 18.0 | 50.0 | 9.0 | 44.0 |
| 9911106 | ● E25-SLSA3.175-35 | HSK-E25 Slim | 3.175 | 6.175 | 17.0 | 8.0 | 8.0 | 18.0 | 35.0 | 9.0 | 29.0 |
| 9911107 | ● E25-SLSA3.175-50 | HSK-E25 Slim | 3.175 | 6.175 | 32.0 | 8.0 | 9.6 | 18.0 | 50.0 | 9.0 | 44.0 |
| 9911108 | ● E25-SLSA4-35 | HSK-E25 Slim | 4.0 | 7.0 | 17.0 | 8.0 | 8.8 | 18.0 | 35.0 | 12.0 | 29.0 |
| 9911109 | ● E25-SLSA4-50 | HSK-E25 Slim | 4.0 | 7.0 | 32.0 | 8.0 | 10.4 | 18.0 | 50.0 | 12.0 | 44.0 |
| 9911110 | ● E25-SLSA5-35 | HSK-E25 Slim | 5.0 | 8.0 | 17.0 | 8.0 | 9.8 | 18.0 | 35.0 | 15.0 | 26.0 |
| 9911111 | ● E25-SLSA6-35 | HSK-E25 Slim | 6.0 | 9.0 | 17.0 | 8.0 | 10.8 | 18.0 | 35.0 | 18.0 | 26.0 |
| 9911112 | ● E25-SLSA6-50 | HSK-E25 Slim | 6.0 | 9.0 | 32.0 | 8.0 | 12.4 | 18.0 | 50.0 | 18.0 | 39.0 |

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

HSK-E32 Mono Series

| EDP Number | Designation | Body Type | Bore Diameter | Nose Diameter | Neck Length | | Neck Diameter | Body Diameter | Overall Length | Clamping Length | Max Insertion Length |
|------------|--------------------|-----------------|---------------|---------------|-------------|---------|---------------|---------------|----------------|-----------------|----------------------|
| | | | d3 (mm) | C (mm) | L1 (mm) | L2 (mm) | d1 (mm) | D3 (mm) | L (mm) | H (mm) | H1 (mm) |
| 9911001 | ● E32-SLRA3-50 | HSK-E32 Regular | 3.0 | 7.5 | 22.0 | 8.0 | 9.9 | 20.0 | 50.0 | 9.0 | 42.0 |
| 9911017 | ● E32-SLRA3-70 | HSK-E32 Regular | 3.0 | 7.5 | 42.0 | 8.0 | 11.9 | 20.0 | 70.0 | 9.0 | 62.0 |
| 9911002 | ● E32-SLRA4-50 | HSK-E32 Regular | 4.0 | 10.0 | 22.0 | 8.0 | 12.4 | 20.0 | 50.0 | 12.0 | 35.0 |
| 9911018 | ● E32-SLRA4-70 | HSK-E32 Regular | 4.0 | 10.0 | 42.0 | 8.0 | 14.4 | 20.0 | 70.0 | 12.0 | 54.0 |
| 9911003 | ● E32-SLRA6-50 | HSK-E32 Regular | 6.0 | 12.0 | 22.0 | 8.0 | 14.4 | 26.0 | 50.0 | 18.0 | 39.0 |
| 9911019 | ● E32-SLRA6-70 | HSK-E32 Regular | 6.0 | 12.0 | 42.0 | 8.0 | 16.4 | 26.0 | 70.0 | 18.0 | 54.0 |
| 9911004 | ● E32-SLRA8-50 | HSK-E32 Regular | 8.0 | 14.0 | 22.0 | 8.0 | 16.4 | 26.0 | 50.0 | 24.0 | 39.0 |
| 9911005 | ● E32-SLRA10-55 | HSK-E32 Regular | 10.0 | 16.0 | 22.0 | 13.0 | 18.4 | 26.0 | 55.0 | 30.0 | 44.0 |
| 9911006 | ● E32-SLRA12-55 | HSK-E32 Regular | 12.0 | 20.0 | 22.0 | 13.0 | 22.4 | 26.0 | 55.0 | 30.0 | 44.0 |
| 9911008 | ● E32-SLSA3-50 | HSK-E32 Slim | 3.0 | 6.0 | 22.0 | 8.0 | 8.4 | 20.0 | 50.0 | 9.0 | 42.0 |
| 9911009 | ● E32-SLSA3-70 | HSK-E32 Slim | 3.0 | 6.0 | 42.0 | 8.0 | 10.5 | 20.0 | 70.0 | 9.0 | 62.0 |
| 9911010 | ● E32-SLSA3.175-50 | HSK-E32 Slim | 3.175 | 6.175 | 22.0 | 8.0 | 8.5 | 20.0 | 50.0 | 9.0 | 42.0 |
| 9911011 | ● E32-SLSA3.175-70 | HSK-E32 Slim | 3.175 | 6.175 | 42.0 | 8.0 | 10.6 | 20.0 | 70.0 | 9.0 | 62.0 |
| 9911012 | ● E32-SLSA4-50 | HSK-E32 Slim | 4.0 | 7.0 | 22.0 | 8.0 | 9.4 | 20.0 | 50.0 | 12.0 | 34.0 |
| 9911013 | ● E32-SLSA4-70 | HSK-E32 Slim | 4.0 | 7.0 | 42.0 | 8.0 | 11.5 | 20.0 | 70.0 | 12.0 | 54.0 |
| 9911014 | ● E32-SLSA5-50 | HSK-E32 Slim | 5.0 | 8.0 | 22.0 | 8.0 | 10.4 | 20.0 | 50.0 | 15.0 | 34.0 |
| 9911015 | ● E32-SLSA5-70 | HSK-E32 Slim | 5.0 | 8.0 | 42.0 | 8.0 | 12.5 | 20.0 | 70.0 | 15.0 | 54.0 |
| 9911016 | ● E32-SLSA6-70 | HSK-E32 Slim | 6.0 | 9.0 | 42.0 | 8.0 | 13.5 | 20.0 | 70.0 | 18.0 | 54.0 |

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX






List 9902 (Continued)

PACKED
1 PIECE

HY-PRO® Shrink Mono Holders, For Standard & Coolant-Through the Tool Operations



HSK-E32 Mono Series

| EDP Number | Designation | Body Type | Bore Diameter | Nose Diameter | Neck Length | | Neck Diameter | Body Diameter | Overall Length | Clamping Length | Max Insertion Length |
|------------|--------------------|-----------------|---------------|---------------|-------------|---------|---------------|---------------|----------------|-----------------|----------------------|
| | | | d3 (mm) | C (mm) | L1 (mm) | L2 (mm) | d1 (mm) | D3 (mm) | L (mm) | H (mm) | H1 (mm) |
| 9911040 | ● E40-SLRA3-50 | HSK-E40 Regular | 3.0 | 7.5 | 22.0 | 8.0 | 9.8 | 20.0 | 50.0 | 9.0 | 42.0 |
| 9911041 | ● E40-SLRA3-70 | HSK-E40 Regular | 3.0 | 7.5 | 42.0 | 8.0 | 11.9 | 20.0 | 70.0 | 9.0 | 62.0 |
| 9911042 | ● E40-SLRA4-50 | HSK-E40 Regular | 4.0 | 10.0 | 22.0 | 8.0 | 12.3 | 20.0 | 50.0 | 12.0 | 42.0 |
| 9911043 | ● E40-SLRA4-70 | HSK-E40 Regular | 4.0 | 10.0 | 42.0 | 8.0 | 14.4 | 20.0 | 70.0 | 12.0 | 62.0 |
| 9911020 | ● E40-SLRA6-50 | HSK-E40 Regular | 6.0 | 12.0 | 22.0 | 8.0 | 14.4 | 26.0 | 50.0 | 18.0 | 39.0 |
| 9911044 | ● E40-SLRA6-70 | HSK-E40 Regular | 6.0 | 12.0 | 42.0 | 8.0 | 16.4 | 26.0 | 70.0 | 18.0 | 54.0 |
| 9911021 | ● E40-SLRA8-50 | HSK-E40 Regular | 8.0 | 14.0 | 22.0 | 8.0 | 16.4 | 26.0 | 50.0 | 24.0 | 39.0 |
| 9911045 | ● E40-SLRA8-85 | HSK-E40 Regular | 8.0 | 14.0 | 42.0 | 23.0 | 18.4 | 25.0 | 85.0 | 24.0 | 69.0 |
| 9911022 | ● E40-SLRA10-55 | HSK-E40 Regular | 10.0 | 16.0 | 22.0 | 13.0 | 18.4 | 26.0 | 55.0 | 30.0 | 44.0 |
| 9911046 | ● E40-SLRA10-85 | HSK-E40 Regular | 10.0 | 16.0 | 42.0 | 23.0 | 20.4 | 25.0 | 85.0 | 30.0 | 64.0 |
| 9911023 | ● E40-SLRA12-55 | HSK-E40 Regular | 12.0 | 20.0 | 22.0 | 13.0 | 22.4 | 30.0 | 55.0 | 30.0 | 44.0 |
| 9911047 | ● E40-SLRA12-85 | HSK-E40 Regular | 12.0 | 20.0 | 42.0 | 23.0 | 24.4 | 32.0 | 85.0 | 30.0 | 74.0 |
| 9911026 | ● E40-SLSA3-50 | HSK-E40 Slim | 3.0 | 6.0 | 22.0 | 8.0 | 8.4 | 20.0 | 50.0 | 9.0 | 42.0 |
| 9911027 | ● E40-SLSA3-70 | HSK-E40 Slim | 3.0 | 6.0 | 42.0 | 8.0 | 10.5 | 20.0 | 70.0 | 9.0 | 62.0 |
| 9911028 | ● E40-SLSA3.175-50 | HSK-E40 Slim | 3.175 | 6.175 | 22.0 | 8.0 | 8.5 | 20.0 | 50.0 | 9.0 | 42.0 |
| 9911029 | ● E40-SLSA3.176-70 | HSK-E40 Slim | 3.175 | 6.175 | 42.0 | 8.0 | 10.6 | 20.0 | 70.0 | 9.0 | 62.0 |
| 9911030 | ● E40-SLSA4-50 | HSK-E40 Slim | 4.0 | 7.0 | 22.0 | 8.0 | 9.4 | 20.0 | 50.0 | 12.0 | 42.0 |
| 9911031 | ● E40-SLSA4-70 | HSK-E40 Slim | 4.0 | 7.0 | 42.0 | 8.0 | 11.5 | 20.0 | 70.0 | 12.0 | 62.0 |
| 9911032 | ● E40-SLSA5-50 | HSK-E40 Slim | 5.0 | 8.0 | 22.0 | 8.0 | 10.4 | 20.0 | 50.0 | 15.0 | 34.0 |
| 9911033 | ● E40-SLSA5-70 | HSK-E40 Slim | 5.0 | 8.0 | 42.0 | 8.0 | 12.5 | 20.0 | 70.0 | 15.0 | 54.0 |
| 9911034 | ● E40-SLSA6-50 | HSK-E40 Slim | 6.0 | 9.0 | 22.0 | 8.0 | 11.4 | 20.0 | 50.0 | 18.0 | 39.0 |
| 9911035 | ● E40-SLSA6-70 | HSK-E40 Slim | 6.0 | 9.0 | 42.0 | 8.0 | 13.5 | 20.0 | 70.0 | 18.0 | 54.0 |
| 9911036 | ● E40-SLSA8-60 | HSK-E40 Slim | 8.0 | 11.0 | 22.0 | 18.0 | 13.4 | 26.0 | 60.0 | 24.0 | 49.0 |
| 9911037 | ● E40-SLSA8-80 | HSK-E40 Slim | 8.0 | 11.0 | 42.0 | 18.0 | 15.5 | 26.0 | 80.0 | 24.0 | 64.0 |
| 9911038 | ● E40-SLSA10-60 | HSK-E40 Slim | 10.0 | 13.0 | 22.0 | 18.0 | 15.4 | 26.0 | 60.0 | 30.0 | 49.0 |
| 9911039 | ● E40-SLSA10-80 | HSK-E40 Slim | 10.0 | 13.0 | 42.0 | 18.0 | 17.5 | 26.0 | 80.0 | 30.0 | 64.0 |

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

