



# Standard Ball Nose Carbide 2 Flute and 3 Flute

## Profiling (Fractional)

Hardness	-		-		<20 HRC		20-30 HRC		30-40 HRC		40-50 HRC	
Work Material	Aluminum		Cast Iron		Mild Carbon Steels Mild Steels		Pre-hardened Steels Die & Alloy Steels		Pre-hardened Steels Die & Alloy Steels		Hardened Steels	
Cutting Speed	330 SFM		115 SFM		115 SFM		80 SFM		65 SFM		82 SFM	
Depth of Cut	$da=0.1D$ $dr=0.2D$ 											
Mill Dia.	Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min
3/64	25,000	5.9	9,365	3.0	9,365	2.6	6,515	1.5	5,295	0.7	6,675	1.5
5/64	16,120	7.6	5,620	3.5	5,620	3.1	3,910	1.8	3,175	0.9	4,005	1.8
1/8	10,075	7.6	3,510	3.7	3,510	3.3	2,445	1.9	1,985	1.1	2,505	2.1
5/32	8,060	7.6	2,810	3.9	2,810	3.5	1,954	2.0	1,590	1.2	2,005	2.2
3/16	6,720	7.9	2,340	4.1	2,340	3.7	1,630	2.0	1,325	1.2	1,670	2.3
1/4	5,040	7.1	1,760	3.6	1,760	3.2	1,220	1.8	990	1.2	1,250	2.1
5/16	4,030	8.8	1,405	3.9	1,405	3.5	975	2.0	795	1.2	1,000	2.2
13/32	3,100	8.4	1,080	3.8	1,080	3.4	750	1.9	610	1.1	770	2.1
15/32	2,685	9.0	935	3.9	935	3.5	650	2.0	530	1.2	670	2.2
5/8	2,015	8.8	700	3.9	700	3.5	490	2.0	395	1.2	500	2.2
25/32	1,610	8.8	560	3.9	560	3.5	390	2.0	320	1.2	400	2.2
1	1,260	9.1	440	3.8	440	3.4	305	1.9	250	1.2	315	2.2

1. Increase speeds & feeds 5-10% for Series 412BN, 414BN, 442BN and 444BN.
2. Reduce speeds & feeds 20-30% for Series 462BN and 464BN.
3. Reduce speeds & feeds 40-50% for Series 482BN and 484BN.
4. Increase speeds & feeds 20-30% for Series 402BN TiN and 404BN TiN.
5. Column for Hardened Steels (40-50 HRC) is for 402BN TiN and 404BN TiN only.

## Profiling (Metric)

Hardness	-		-		<20 HRC		20-30 HRC		30-40 HRC		40-50 HRC	
Work Material	Aluminum		Cast Iron		Mild Carbon Steels Mild Steels		Pre-hardened Steels Die & Alloy Steels		Pre-hardened Steels Die & Alloy Steels		Hardened Steels	
Cutting Speed	330 SFM		115 SFM		115 SFM		80 SFM		65 SFM		82 SFM	
Depth of Cut	$da=0.1D$ $dr=0.2D$ 											
Mill Dia.	Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min
1	25,000	5.8	11,130	3.6	11,130	3.2	7,950	1.8	6,360	0.9	7,950	1.8
2	15,905	7.4	5,565	3.5	5,565	3.1	3,975	1.8	3,180	0.9	3,975	1.8
3	10,600	7.9	3,710	3.9	3,710	3.6	2,650	2.0	2,120	1.2	2,650	2.2
4	7,950	7.4	2,785	3.9	2,785	3.5	1,990	2.0	1,590	1.2	1,990	2.2
5	6,360	7.4	2,225	4.0	2,225	3.6	1,590	2.0	1,270	1.2	1,590	2.2
6	5,300	7.5	1,855	3.8	1,855	3.5	1,325	2.0	1,060	1.3	1,325	2.2
8	3,975	8.6	1,390	3.9	1,390	3.5	995	2.0	795	1.2	995	2.2
10	3,180	8.6	1,115	4.0	1,115	3.6	795	2.0	635	1.2	795	2.2
12	2,650	8.8	930	3.9	930	3.5	665	2.0	530	1.2	665	2.2
16	1,990	8.6	695	3.9	695	3.5	495	1.9	400	1.2	495	2.1
20	1,590	8.6	555	3.9	555	3.5	400	2.0	320	1.2	400	2.2
25	1,270	9.2	445	3.9	445	3.5	320	2.0	255	1.2	320	2.2

1. Increase speeds & feeds 5-10% for Series 412BN, 414BN, 442BN and 444BN.
2. Reduce speeds & feeds 20-30% for Series 462BN and 464BN.
3. Reduce speeds & feeds 40-50% for Series 482BN and 484BN.
4. Increase speeds & feeds 20-30% for Series 402BN TiN and 404BN TiN.
5. Column for Hardened Steels (40-50 HRC) is for 402BN TiN and 404BN TiN only.

