



List 8830, 8930, 8870, 8970: 3-Flute, Regular Length, Reduced Neck

Slotting

Work Material		Aluminum Alloys, Magnesium Alloys A5052, A6061, A7075, AZ91, AZ80A		Aluminum Alloy Casting AC4C, ADC		Copper Alloy C1100	
Cutting Speed		600 - 1700 SFM		600 - 1700 SFM		400 - 1000 SFM	
Depth of Cut		Aa=1xD				Aa=0.5xD	
Mill Dia.		Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min
Inch	mm						
-	1	25,000	25.0	25,000	25.0	25,000	25.0
-	1.5	25,000	37.5	25,000	37.5	25,000	37.5
-	2	25,000	50.0	25,000	50.0	25,000	50.0
-	2.5	25,000	62.5	25,000	62.5	25,000	62.5
-	3	25,000	79.7	25,000	79.7	22,600	72.1
1/8	-	25,000	88.6	25,000	88.6	21,400	75.8
-	4	25,000	102.8	25,000	102.8	17,000	69.9
3/16	-	25,000	118.1	25,000	118.1	14,200	67.1
-	5	25,000	128.4	25,000	128.4	13,600	69.9
-	6	21,000	129.5	21,000	129.5	11,300	69.7
1/4	-	19,800	128.6	19,800	128.6	10,700	69.5
5/16	-	15,900	131.5	15,900	131.5	8,500	70.3
-	8	15,800	129.9	15,800	129.9	8,500	69.9
3/8	-	13,200	124.7	13,200	124.7	7,100	67.1
-	10	12,600	129.5	12,600	129.5	6,800	69.9
-	12	10,500	129.5	10,500	129.5	5,700	70.3
1/2	-	9,900	128.6	9,900	128.6	5,300	68.9

1. The above milling condition is a guideline for the overhang length is 4xD.
2. Use a rigid and precise machine and holder.
3. The indicated speeds and feeds are for milling with water-soluble coolant.
4. Please adjust the speed and feed when the cutting depth is large or when machines with low rigidity are used.
5. Reduce speed and feed as well as depth of cut when high precision is required.
6. Adjust the speed and feed accordingly when the overhang length is longer than specified (refer to p.1352).
7. Please always use the appropriate cutting fluid recommended by the cutting fluid manufacturer in the machining of magnesium alloys.
Be cautious with the cutting chips as they are highly flammable and may pose a serious fire risk if not properly handled.

Side Milling

Work Material		Aluminum Alloys, Magnesium Alloys A5052, A6061, A7075, AZ91, AZ80A		Aluminum Alloy Casting AC4C, ADC		Copper Alloy C1100	
Cutting Speed		800 - 2200 SFM		800 - 2200 SFM		600 - 1200 SFM	
Depth of Cut		Aa = 1.5xD Ar = 0.2xD				Aa = 1.5xD Ar = 0.1xD	
Mill Dia.		Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min
Inch	mm						
-	1	25,000	25.0	25,000	25.0	25,000	25.0
-	1.5	25,000	37.5	25,000	37.5	25,000	37.5
-	2	25,000	50.0	25,000	50.0	25,000	50.0
-	2.5	25,000	62.5	25,000	62.5	25,000	62.5
-	3	25,000	79.7	25,000	79.7	25,000	79.7
1/8	-	25,000	88.6	25,000	88.6	25,000	88.6
-	4	25,000	102.8	25,000	102.8	21,800	89.6
3/16	-	25,000	118.1	25,000	118.1	18,300	86.5
-	5	25,000	128.4	25,000	128.4	17,500	89.9
-	6	25,000	154.1	25,000	154.1	14,500	89.4
1/4	-	25,000	162.4	25,000	162.4	13,700	89.0
5/16	-	20,800	172.0	20,800	172.0	11,000	90.9
-	8	20,600	169.3	20,600	169.3	10,900	89.6
3/8	-	17,300	163.5	17,300	163.5	9,200	86.9
-	10	16,500	169.5	16,500	169.5	8,700	89.4
-	12	13,700	168.9	13,700	168.9	7,300	90.0
1/2	-	13,000	168.9	13,000	168.9	6,900	89.7

1. The above milling condition is a guideline for the overhang length is 4xD.
2. Use a rigid and precise machine and holder.
3. The indicated speeds and feeds are for milling with water-soluble coolant.
4. Please adjust the speed and feed when the cutting depth is large or when machines with low rigidity are used.
5. Reduce speed and feed as well as depth of cut when high precision is required.
6. Adjust the speed and feed accordingly when the overhang length is longer than specified (refer to p.1352).
7. Please always use the appropriate cutting fluid recommended by the cutting fluid manufacturer in the machining of magnesium alloys.
Be cautious with the cutting chips as they are highly flammable and may pose a serious fire risk if not properly handled.

CONTINUED





A Brand AE-VTS-N & AE-CR-VTS-N

Advanced Performance DLC Coated End Mills for Non-Ferrous Materials

List 8830, 8930, 8870, 8970: 3-Flute, Regular Length, Reduced Neck (Continued)

Plunging

Work Material		Aluminum Alloys, Magnesium Alloys A5052, A6061, A7075, AZ91, AZ80A		Aluminum Alloy Casting AC4C, ADC		Copper Alloy C1100	
Cutting Speed		495 SFM		495 SFM		248 SFM	
Depth of Cut		Aa = 1xD				Aa = 0.5xD	
Mill Dia.		Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM	Feed in/min
Inch	mm						
-	1	20000	15.7	20000	15.7	10000	4.7
-	1.5	20000	15.7	20000	15.7	10000	4.7
-	2	20000	15.7	20000	15.7	10000	4.7
-	2.5	20000	15.7	20000	15.7	10000	4.7
-	3	15,900	19.7	15,900	19.7	8,000	5.9
1/8	-	15,110	19.8	15,110	19.8	7,570	6.0
-	4	12,000	19.7	12,000	19.7	6,000	5.9
3/16	-	10,070	19.8	10,070	19.8	5,040	6.0
-	5	9,600	19.7	9,600	19.7	4,800	5.9
-	6	8,000	23.6	8,000	23.6	4,000	7.1
1/4	-	7,550	23.8	7,550	23.8	3,780	7.1
5/16	-	6,040	23.8	6,040	23.8	3,020	7.1
-	8	6,000	27.6	6,000	27.6	3,000	8.3
3/8	-	5,030	27.7	5,030	27.7	2,520	8.2
-	10	4,800	27.6	4,800	27.6	2,400	8.3
-	12	4,000	27.6	4,000	27.6	2,000	8.3
1/2	-	3,770	27.7	3,770	27.7	1,890	8.2

1. The above milling condition is a guideline for the overhang length is 4xD.
2. Use a rigid and precise machine and holder.
3. The indicated speeds and feeds are for milling with water-soluble coolant.
4. Please adjust the speed and feed when the cutting depth is large or when machines with low rigidity are used.
5. Reduce speed and feed as well as depth of cut when high precision is required.
6. Adjust the speed and feed accordingly when the overhang length is longer than specified (See table below).
7. Please always use the appropriate cutting fluid recommended by the cutting fluid manufacturer in the machining of magnesium alloys.
Be cautious with the cutting chips as they are highly flammable and may pose a serious fire risk if not properly handled.

Cutting Condition Guide for Changes in Overhang Length

	Work Material	Aluminum Alloys, Magnesium Alloys A5052, A6061, A7075, AZ91, AZ80A		Aluminum Alloy Casting AC4C, ADC		Copper Alloy C1100	
		L/D	Speed RPM	Feed in/min	Speed RPM	Feed in/min	Speed RPM
Slotting	5	70%		70%		70%	
	6	50%		50%		50%	
Side Milling	5	70%		70%		70%	
	6	50%		50%		50%	
Plunging	5	80%		80%		80%	
	6	60%		60%		60%	

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

