

A Brand A-Pipe

Advanced Performance Pipe Taps

List 16581

A BRAND A-BSPP-G, Made to G Spec.



EDP		Thread Size	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1658101008	●	1/8 - 28 BSPP	3.543	0.591	1.457	0.313	0.234	0.375	3
1658102008	●	1/4 - 19 BSPP	3.937	0.748	1.929	0.563	0.421	0.438	3
1658103008	●	3/8 - 19 BSPP	3.937	0.827	1.969	0.700	0.531	0.500	4
1658104008	●	1/2 - 14 BSPP	4.921	1.024	2.362	0.688	0.515	0.625	4
1658105008	●	3/4 - 14 BSPP	5.511	1.102	2.913	0.906	0.679	0.688	4
1658106008	●	1 - 11 BSPP	6.299	1.299	3.150	1.125	0.843	0.813	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: A Brand A-BSPP-G is made to ISO 228 standard.



P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium							
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1018	1045				○	○		○		○		○	○						
5-35 SFM	5-35 SFM	5-35 SFM	5-20 SFM	5-20 SFM	5-20 SFM	5-20 SFM		5-20 SFM		5-35 SFM		5-10 SFM	5-20 SFM						

○ Good ○ Best

